

Statement of Basis of the Federal Operating Permit

Occidental Chemical Corporation

Site Name: Ingleside Plant
Physical Location: 4133 Highway 361
Nearest City: Gregory
County: San Patricio

Permit Number: O1240
Project Type: Minor Revision

Standard Industrial Classification (SIC) Code: 2812
SIC Name: Alkalies and Chlorine

This Statement of Basis sets forth the legal and factual basis for the draft changes to the permit conditions resulting from the minor revision project in accordance with 30 TAC §122.201(a)(4). The applicant has submitted an application for a minor permit revision per §§ 122.215-217. This document may include the following information:

- A description of the facility/area process description;
- A description of the revision project;
- A basis for applying permit shields;
- A list of the federal regulatory applicability determinations;
- A table listing the determination of applicable requirements;
- A list of the New Source Review Requirements;
- The rationale for periodic monitoring methods selected;
- The rationale for compliance assurance methods selected;
- A compliance status; and
- A list of available unit attribute forms.

Prepared on: February 8, 2017

Operating Permit Basis of Determination

Description of Revisions

This minor revision is for incorporation by reference of the renewal of NSR permit 2339A, and for removal of term and condition 24 which was for industrial hazardous waste permit HW50322, since the permit does not include an Air Addendum.

Permit Area Process Description

Chlorine and sodium hydroxide at the Ingleside Chemical Plant are made by the electrolysis of saturated sodium chloride brine in an electrolytic cell. The primary steps for chlorine production include: receipt and processing of raw brine, brine electrolysis, chlorine processing and purification, hydrogen processing and purification, caustic processing and purification.

Support services for the chlor-alkali plant include: cell renewal operations, wastewater treatment, cooling tower, chlorine unloading, and emergency power.

FOPs at Site

The “application area” consists of the emission units and that portion of the site included in the application and this permit. Multiple FOPs may be issued to a site in accordance with 30 TAC § 122.201(e). When there is only one area for the site, then the application information and permit will include all units at the site. Additional FOPs that exist at the site, if any, are listed below.

Additional FOPs: O3806

Major Source Pollutants

The table below specifies the pollutants for which the site is a major source:

Major Pollutants	VOC, PM, NOX, HAPS, CO, GHG
------------------	-----------------------------

Reading State of Texas’s Federal Operating Permit

The Title V Federal Operating Permit (FOP) lists all state and federal air emission regulations and New Source Review (NSR) authorizations (collectively known as “applicable requirements”) that apply at a particular site or permit area (in the event a site has multiple FOPs). **The FOP does not authorize new emissions or new construction activities.** The FOP begins with an introductory page which is common to all Title V permits. This page gives the details of the company, states the authority of the issuing agency, requires the company to operate in accordance with this permit and 30 Texas Administrative Code (TAC) Chapter 122, requires adherence with NSR requirements of 30 TAC Chapter 116, and finally indicates the permit number and the issuance date.

This is followed by the table of contents, which is generally composed of the following elements. Not all permits will have all of the elements.

- General Terms and Conditions
- Special Terms and Conditions
 - Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting
 - Additional Monitoring Requirements
 - New Source Review Authorization Requirements
 - Compliance Requirements
 - Protection of Stratosphere Ozone
 - Permit Location
 - Permit Shield (30 TAC § 122.148)

- Attachments
 - Applicable Requirements Summary
 - Unit Summary
 - Applicable Requirements Summary
 - Additional Monitoring Requirements
 - Permit Shield
 - New Source Review Authorization References
 - Compliance Plan
 - Alternative Requirements
- Appendix A
 - Acronym list
- Appendix B
 - Copies of major NSR authorizations

General Terms and Conditions

The General Terms and Conditions are the same and appear in all permits. The first paragraph lists the specific citations for 30 TAC Chapter 122 requirements that apply to all Title V permit holders. The second paragraph describes the requirements for record retention. The third paragraph provides details for voiding the permit, if applicable. The fourth paragraph states that the permit holder shall comply with the requirements of 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit. The fifth paragraph provides details on submission of reports required by the permit.

Special Terms and Conditions

Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting. The TCEQ has designated certain applicable requirements as site-wide requirements. A site-wide requirement is a requirement that applies uniformly to all the units or activities at the site. Units with only site-wide requirements are addressed on Form OP-REQ1 and are not required to be listed separately on a OP-UA Form or Form OP-SUM. Form OP-SUM must list all units addressed in the application and provide identifying information, applicable OP-UA Forms, and preconstruction authorizations. The various OP-UA Forms provide the characteristics of each unit from which applicable requirements are established. Some exceptions exist as a few units may have both site-wide requirements and unit specific requirements.

Other conditions. The other entries under special terms and conditions are in general terms referring to compliance with the more detailed data listed in the attachments.

Attachments

Applicable Requirements Summary. The first attachment, the Applicable Requirements Summary, has two tables, addressing unit specific requirements. The first table, the Unit Summary, includes a list of units with applicable requirements, the unit type, the applicable regulation, and the requirement driver. The intent of the requirement driver is to inform the reader that a given unit may have several different operating scenarios and the differences between those operating scenarios.

The applicable requirements summary table provides the detailed citations of the rules that apply to the various units. For each unit and operating scenario, there is an added modifier called the “index number,” detailed citations specifying monitoring and testing requirements, recordkeeping requirements, and reporting requirements. The data for this table are based on data supplied by the applicant on the OP-SUM and various OP-UA forms.

Additional Monitoring Requirement. The next attachment includes additional monitoring the applicant must perform to ensure compliance with the applicable standard. Compliance assurance monitoring (CAM) is often required to provide a reasonable assurance of compliance with applicable emission limitations/standards for large emission units that use control devices to achieve compliance with applicant requirements. When

necessary, periodic monitoring (PM) requirements are specified for certain parameters (i.e. feed rates, flow rates, temperature, fuel type and consumption, etc.) to determine if a term and condition or emission unit is operating within specified limits to control emissions. These additional monitoring approaches may be required for two reasons. First, the applicable rules do not adequately specify monitoring requirements (exception- Maximum Achievable Control Technology Standards (MACTs) generally have sufficient monitoring), and second, monitoring may be required to fill gaps in the monitoring requirements of certain applicable requirements. In situations where the NSR permit is the applicable requirement requiring extra monitoring for a specific emission unit, the preferred solution is to have the monitoring requirements in the NSR permit updated so that all NSR requirements are consolidated in the NSR permit.

Permit Shield. A permit may or may not have a permit shield, depending on whether an applicant has applied for, and justified the granting of, a permit shield. A permit shield is a special condition included in the permit document stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirement(s) or specified applicable state-only requirement(s).

New Source Review Authorization References. All activities which are related to emissions in the state of Texas must have a NSR authorization prior to beginning construction. This section lists all units in the permit and the NSR authorization that allowed the unit to be constructed or modified. Units that do not have unit specific applicable requirements other than the NSR authorization do not need to be listed in this attachment. While NSR permits are not physically a part of the Title V permit, they are legally incorporated into the Title V permit by reference. Those NSR permits whose emissions exceed certain PSD/NA thresholds must also undergo a Federal review of federally regulated pollutants in addition to review for state regulated pollutants.

Compliance Plan. A permit may have a compliance schedule attachment for listing corrective actions plans for any emission unit that is out of compliance with an applicable requirement.

Alternative Requirements. This attachment will list any alternative monitoring plans or alternative means of compliance for applicable requirements that have been approved by the EPA Administrator and/or the TCEQ Executive Director.

Appendix A

Acronym list. This attachment lists the common acronyms used when discussing the FOPs.

Appendix B

Copies of major NSR authorizations applicable to the units covered by this permit have been included in this Appendix, to ensure that all interested persons can access those authorizations.

Stationary vents subject to 30 TAC Chapter 111, Subchapter A, § 111.111(a)(1)(B) addressed in the Special Terms and Conditions

The site contains stationary vents with a flowrate less than 100,000 actual cubic feet per minute (acfm) and constructed after January 31, 1972 which are limited, over a six-minute average, to 20% opacity as required by 30 TAC § 111.111(a)(1)(B). As a site may have a large number of stationary vents that fall into this category, they are not required to be listed individually in the permit's Applicable Requirement Summary. This is consistent with EPA's White Paper for Streamlined Development of Part 70 Permit Applications, July 10, 1995, that states that requirements that apply identically to emission units at a site can be treated on a generic basis such as source-wide opacity limits.

Periodic monitoring is specified in Special Term and Condition 3.A. for stationary vents subject to 30 TAC § 111.111(a)(1)(B) to verify compliance with the 20% opacity limit. These vents are not expected to produce visible emissions during normal operation. The TCEQ evaluated the probability of these sources violating the opacity standards and determined that there is a very low potential that an opacity standard would be exceeded. It was determined that continuous monitoring for these sources is not warranted as there would be very limited environmental benefit in continuously monitoring sources that have a low potential to produce

visible emissions. Therefore, the TCEQ set the visible observation monitoring frequency for these sources to once per calendar quarter.

The TCEQ has exempted vents that are not capable of producing visible emissions from periodic monitoring requirements. These vents include sources of colorless VOCs, non-fuming liquids, and other materials that cannot produce emissions that obstruct the transmission of light. Passive ventilation vents, such as plumbing vents, are also included in this category. Since this category of vents are not capable of producing opacity due to the physical or chemical characteristics of the emission source, periodic monitoring is not required as it would not yield any additional data to assure compliance with the 20% opacity standard of 30 TAC § 111.111(a)(1)(B).

In the event that visible emissions are detected, either through the quarterly observation or other credible evidence, such as observations from company personnel, the permit holder shall either report a deviation or perform a Test Method 9 observation to determine the opacity consistent with the 6-minute averaging time specified in 30 TAC § 111.111(a)(1)(B). An additional provision is included to monitor combustion sources more frequently than quarterly if alternate fuels are burned for periods greater than 24 consecutive hours. This will address possible emissions that may arise when switching fuel types.

Stationary Vents subject to 30 TAC Chapter 111 not addressed in the Special Terms and Conditions

All other stationary vents subject to 30 TAC Chapter 111 not covered in the Special Terms and Conditions are listed in the permit's Applicable Requirement Summary. The basis for the applicability determinations for these vents are listed in the Determination of Applicable Requirements table.

Federal Regulatory Applicability Determinations

The following chart summarizes the applicability of the principal air pollution regulatory programs to the permit area:

Regulatory Program	Applicability (Yes/No)
Prevention of Significant Deterioration (PSD)	Yes
Nonattainment New Source Review (NNSR)	No
Minor NSR	Yes
40 CFR Part 60 - New Source Performance Standards	Yes
40 CFR Part 61 - National Emission Standards for Hazardous Air Pollutants (NESHAPs)	Yes
40 CFR Part 63 - NESHAPs for Source Categories	Yes
Title IV (Acid Rain) of the Clean Air Act (CAA)	No
Title V (Federal Operating Permits) of the CAA	Yes
Title VI (Stratospheric Ozone Protection) of the CAA	Yes
CAIR (Clean Air Interstate Rule)	No

Insignificant Activities

In general, units not meeting the criteria for inclusion on either Form OP-SUM or Form OP-REQ1 are not required to be addressed in the operating permit application. Examples of these types of units include, but are not limited to, the following:

1. Office activities such as photocopying, blueprint copying, and photographic processes.
2. Sanitary sewage collection and treatment facilities other than those used to incinerate wastewater treatment plant sludge. Stacks or vents for sanitary sewer plumbing traps are also included.
3. Food preparation facilities including, but not limited to, restaurants and cafeterias used for preparing food or beverages primarily for consumption on the premises.
4. Outdoor barbecue pits, campfires, and fireplaces.
5. Laundry dryers, extractors, and tumblers processing bedding, clothing, or other fabric items generated primarily at the premises. This does not include emissions from dry cleaning systems using perchloroethylene or petroleum solvents.
6. Facilities storing only dry, sweet natural gas, including natural gas pressure regulator vents.
7. Any air separation or other industrial gas production, storage, or packaging facility. Industrial gases, for purposes of this list, include only oxygen, nitrogen, helium, neon, argon, krypton, and xenon.
8. Storage and handling of sealed portable containers, cylinders, or sealed drums.
9. Vehicle exhaust from maintenance or repair shops.
10. Storage and use of non-VOC products or equipment for maintaining motor vehicles operated at the site (including but not limited to, antifreeze and fuel additives).
11. Air contaminant detectors and recorders, combustion controllers and shut-off devices, product analyzers, laboratory analyzers, continuous emissions monitors, other analyzers and monitors, and emissions associated with sampling activities. Exception to this category includes sampling activities that are deemed fugitive emissions and under a regulatory leak detection and repair program.
12. Bench scale laboratory equipment and laboratory equipment used exclusively for chemical and physical analysis, including but not limited to, assorted vacuum producing devices and laboratory fume hoods.
13. Steam vents, steam leaks, and steam safety relief valves, provided the steam (or boiler feedwater) has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
14. Storage of water that has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
15. Well cellars.
16. Fire or emergency response equipment and training, including but not limited to, use of fire control equipment including equipment testing and training, and open burning of materials or fuels associated with firefighting training.
17. Crucible or pot furnaces with a brim full capacity of less than 450 cubic inches of any molten metal.
18. Equipment used exclusively for the melting or application of wax.
19. All closed tumblers used for the cleaning or deburring of metal products without abrasive blasting, and all open tumblers with a batch capacity of 1,000 lbs. or less.
20. Shell core and shell mold manufacturing machines.
21. Sand or investment molds with a capacity of 100 lbs. or less used for the casting of metals;
22. Equipment used for inspection of metal products.
23. Equipment used exclusively for rolling, forging, pressing, drawing, spinning, or extruding either hot or cold metals by some mechanical means.
24. Instrument systems utilizing air, natural gas, nitrogen, oxygen, carbon dioxide, helium, neon, argon, krypton, and xenon.
25. Battery recharging areas.
26. Brazing, soldering, or welding equipment.

Determination of Applicable Requirements

The tables below include the applicability determinations for the emission units, the index number(s) where applicable, and all relevant unit attribute information used to form the basis of the applicability determination. The unit attribute information is a description of the physical properties of an emission unit which is used to determine the requirements to which the permit holder must comply. For more information about the descriptions of the unit attributes specific Unit Attribute Forms may be viewed at www.tceq.texas.gov/permitting/air/nav/air_all_ua_forms.html.

A list of unit attribute forms is included at the end of this document. Some examples of unit attributes include construction date; product stored in a tank; boiler fuel type; etc.. Generally, multiple attributes are needed to determine the requirements for a given emission unit and index number. The table below lists these attributes in the column entitled "Basis of Determination." Attributes that demonstrate that an applicable requirement applies will be the factual basis for the specific citations in an applicable requirement that apply to a unit for that index number. The TCEQ Air Permits Division has developed flowcharts for determining applicability of state and federal regulations based on the unit attribute information in a Decision Support System (DSS). These flowcharts can be accessed via the internet at www.tceq.texas.gov/permitting/air/nav/air_supportsys.html. The Air Permits Division staff may also be contacted for assistance at (512) 239-1250.

The attributes for each unit and corresponding index number provide the basis for determining the specific legal citations in an applicable requirement that apply, including emission limitations or standards, monitoring, recordkeeping, and reporting. The rules were found to apply or not apply by using the unit attributes as answers to decision questions found in the flowcharts of the DSS. Some additional attributes indicate which legal citations of a rule apply. The legal citations that apply to each emission unit may be found in the Applicable Requirements Summary table of the draft permit. There may be some entries or rows of units and rules not found in the permit, or if the permit contains a permit shield, repeated in the permit shield area. These are sets of attributes that describe negative applicability, or; in other words, the reason why a potentially applicable requirement does not apply.

If applicability determinations have been made which differ from the available flowcharts, an explanation of the decisions involved in the applicability determination is specified in the column "Changes and Exceptions to RRT." If there were no exceptions to the DSS, then this column has been removed.

The draft permit includes all emission limitations or standards, monitoring, recordkeeping and reporting required by each applicable requirement. If an applicable requirement does not require monitoring, recordkeeping, or reporting, the word "None" will appear in the Applicable Requirements Summary table. If additional periodic monitoring is required for an applicable requirement, it will be explained in detail in the portion of this document entitled "Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected."

When attributes demonstrate that a unit is not subject to an applicable requirement, the applicant may request a permit shield for those items. The portion of this document entitled "Basis for Applying Permit Shields" specifies which units, if any, have a permit shield.

Operational Flexibility

When an emission unit has multiple operating scenarios, it will have a different index number associated with each operating condition. This means that units are permitted to operate under multiple operating conditions. The applicable requirements for each operating condition are determined by a unique set of unit attributes. For example, a tank may store two different products at different points in time. The tank may, therefore, need to comply with two distinct sets of requirements, depending on the product that is stored. Both sets of requirements are included in the permit, so that the permit holder may store either product in the tank.

Determination of Applicable Requirements

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
PLTBlast	R1111-PLTBlast	R1111-PLTBlast	UNIT TYPE = EMISSION UNIT FUNCTIONALLY IDENTICAL REPLACEMENT [REG VII] = UNIT IS NOT FUNCTIONALLY IDENTICAL REPLACEMENT (DATE CONSTRUCTED/PLACED IN SERVICE = '92+')	Main Standard Requirement - § 111.111(a)(8)(A) was added for the addition of case-by-case periodic monitoring. Monitoring and Testing Requirement - § 111.111(a)(8)(A) was added for the addition of case-by-case periodic monitoring.
PLTPaint	R1111-PLTPaint	R1111-PLTPaint	UNIT TYPE = EMISSION UNIT FUNCTIONALLY IDENTICAL REPLACEMENT [REG VII] = UNIT IS NOT FUNCTIONALLY IDENTICAL REPLACEMENT (DATE CONSTRUCTED/PLACED IN SERVICE = '92+')	Main Standard Requirement - § 111.111(a)(8)(A) was added for the addition of case-by-case periodic monitoring. Monitoring and Testing Requirement - § 111.111(a)(8)(A) was added for the addition of case-by-case periodic monitoring.
VCM-20	R1111-VCM-20	R1111-VCM-20	UNIT TYPE = EMISSION UNIT FUNCTIONALLY IDENTICAL REPLACEMENT [REG VII] = UNIT IS NOT FUNCTIONALLY IDENTICAL REPLACEMENT (DATE CONSTRUCTED/PLACED IN SERVICE = '92+')	Main Standard Requirement - § 111.111(a)(8)(A) was added for the addition of case-by-case periodic monitoring. Monitoring and Testing Requirement - § 111.111(a)(8)(A) was added for the addition of case-by-case periodic monitoring.
VCM-21	R1111-VCM-21	R1111-VCM-21	UNIT TYPE = EMISSION UNIT FUNCTIONALLY IDENTICAL REPLACEMENT [REG VII] = UNIT IS NOT FUNCTIONALLY IDENTICAL REPLACEMENT (DATE CONSTRUCTED/PLACED IN SERVICE = '92+')	Main Standard Requirement - § 111.111(a)(8)(A) was added for the addition of case-by-case periodic monitoring. Monitoring and Testing Requirement - § 111.111(a)(8)(A) was added in for the addition of case-by-case periodic monitoring.
VCM-4	R1111-VCM-4	R1111-VCM-4	UNIT TYPE = EMISSION UNIT FUNCTIONALLY IDENTICAL REPLACEMENT [REG VII] = UNIT IS NOT FUNCTIONALLY IDENTICAL REPLACEMENT (DATE CONSTRUCTED/PLACED IN SERVICE = '92+')	Main Standard Requirement - § 111.111(a)(8)(A) was added for the addition of case-by-case periodic monitoring. Monitoring and Testing Requirement - § 111.111(a)(8)(A) was added for the addition of case-by-case periodic monitoring.
YARDBlast	R1111-YARDBlast	R1111-YARDBlast	UNIT TYPE = EMISSION UNIT FUNCTIONALLY IDENTICAL REPLACEMENT [REG VII] = UNIT IS NOT FUNCTIONALLY IDENTICAL REPLACEMENT (DATE CONSTRUCTED/PLACED IN SERVICE = '92+')	Main Standard Requirement - § 111.111(a)(8)(A) was added for the addition of case-by-case periodic monitoring. Monitoring and Testing Requirement - § 111.111(a)(8)(A) was added for the addition of case-by-case periodic monitoring.
YARDPaint	R1111-YDPaint	R1111-YDPaint	UNIT TYPE = EMISSION UNIT FUNCTIONALLY IDENTICAL REPLACEMENT [REG VII] = UNIT IS NOT FUNCTIONALLY IDENTICAL REPLACEMENT (DATE CONSTRUCTED/PLACED IN	Main Standard Requirement - § 111.111(a)(8)(A) was added for the addition of case-by-case periodic monitoring.

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			SERVICE = '92+')	Monitoring and Testing Requirement - § 111.111(a)(8)(A) was added for the addition of case-by-case periodic monitoring.
263	40 CFR Part 60, Subpart IIII	60IIII-EMERGEN	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after July 11, 2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating is greater than 560 KW and less than or equal to 2237 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Displacement = Displacement is less than 10 liters per cylinder and engine is a constant-speed engine.</p> <p>Service = CI ICE is an emergency engine.</p> <p>Standards = The emergency CI ICE does not meet the standards applicable to non-emergency engines.</p> <p>Commencing = CI ICE that is commencing new construction.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Manufacture Date = Date of manufacture is after 04/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2008.</p> <p>Install Date = The CI ICE was installed prior to 2012.</p>	Reporting requirement [G]§ 60.4214(d) was removed since it does not apply to emergency engines.
263	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = 4 stroke spark ignited rich burn engine</p>	
354	40 CFR Part 60, Subpart IIII	60IIII-EMERGEN	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after July 11, 2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating is greater than 560 KW and less than or equal to 2237 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Displacement = Displacement is less than 10 liters per cylinder and engine is a constant-speed engine.</p> <p>Service = CI ICE is an emergency engine.</p> <p>Standards = The emergency CI ICE does not meet the standards applicable to non-</p>	Reporting requirement [G]§ 60.4214(d) was removed since it does not apply to emergency engines.

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>emergency engines.</p> <p>Commencing = CI ICE that is commencing new construction.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Manufacture Date = Date of manufacture is after 04/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2007.</p> <p>Install Date = The CI ICE was installed prior to 2012.</p>	
354	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-1	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = 4 stroke spark ignited rich burn engine</p>	
EGEN-3	40 CFR Part 63, Subpart ZZZZ	63ZZZZ	<p>Brake HP = Stationary RICE with a brake HP greater than 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p>	
EGEN-4	40 CFR Part 60, Subpart IIII	60IIII-EMERGEN	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after July 11, 2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating greater than or equal to 130 KW and less than or equal to 368 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Displacement = Displacement is less than 10 liters per cylinder and engine is a constant-speed engine.</p> <p>Service = CI ICE is an emergency engine.</p> <p>Standards = The emergency CI ICE does not meet the standards applicable to non-emergency engines.</p> <p>Commencing = CI ICE that is commencing new construction.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Manufacture Date = Date of manufacture is after 04/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2012.</p> <p>Install Date = The CI ICE was installed in 2012 or later.</p>	Reporting requirement [G]§ 60.4214(d) was removed since it does not apply to emergency engines.
EGEN-4	40 CFR Part 63,	63ZZZZ-2	HAP Source = Any stationary source or group of stationary sources of hazardous air	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart ZZZZ		<p>pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p>	
ENGSTK3	40 CFR Part 60, Subpart IIII	60IIII-EMERFWP	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after July 11, 2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating is greater than or equal to 130 KW and less than or equal to 368 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Displacement = Displacement is less than 10 liters per cylinder.</p> <p>Service = CI ICE is a fire-pump engine, an emergency engine certified to National Fire Protection Association requirements.</p> <p>Standards = The emergency CI ICE does not meet the standards applicable to non-emergency engines.</p> <p>Commencing = CI ICE that is commencing new construction.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Manufacture Date = Date of manufacture is after 07/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2012.</p> <p>Install Date = The CI ICE was installed in 2012 or later.</p>	Reporting requirement [G]§ 60.4214(d) was removed since it does not apply to emergency engines.
ENGSTK3	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-2	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p>	
GRPENG-3	40 CFR Part 60, Subpart IIII	60IIII-EMERFWP	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after July 11, 2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating is greater than or equal to 130 KW and less than or equal</p>	Reporting requirement [G]§ 60.4214(d) was removed since it does not apply to emergency engines.

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>to 368 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Displacement = Displacement is less than 10 liters per cylinder.</p> <p>Service = CI ICE is a fire-pump engine, an emergency engine certified to National Fire Protection Association requirements.</p> <p>Standards = The emergency CI ICE does not meet the standards applicable to non-emergency engines.</p> <p>Commencing = CI ICE that is commencing new construction.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Manufacture Date = Date of manufacture is after 07/01/2006.</p> <p>Model Year = CI ICE was manufactured in model year 2014.</p> <p>Install Date = The CI ICE was installed in 2012 or later.</p>	
GRPENG-3	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-3	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Service Type = Emergency use where the RICE does not operate or is not contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or does not operate as specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>	
YARDENG	40 CFR Part 60, Subpart IIII	60IIII-BLSTCOMP	<p>Applicability Date = Stationary CI ICE commenced construction, reconstruction, or modification after July 11, 2005.</p> <p>Diesel = Diesel fuel is used.</p> <p>Kilowatts = Power rating greater than or equal to 130 KW and less than or equal to 368 KW.</p> <p>Exemptions = The CI ICE is not exempt due to national security, testing at an engine test cell/stand or as a temporary replacement.</p> <p>Filter = The CI ICE is equipped with a diesel particulate filter.</p> <p>Displacement = Displacement is less than 10 liters per cylinder and engine is a constant-speed engine.</p> <p>Service = CI ICE is a non-emergency engine.</p> <p>Commencing = CI ICE that is commencing new construction.</p> <p>Compliance Option = The CI ICE and control device is installed, configured, operated, and maintained according to the manufacturer's emission-related written instructions.</p> <p>Manufacture Date = Date of manufacture is after 04/01/2006.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Model Year = CI ICE was manufactured in model year 2011. Install Date = The CI ICE was installed in 2012 through 2015.	
YARDENG	40 CFR Part 63, Subpart ZZZZ	63ZZZZ-EMERCOMP	HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2. Brake HP = Stationary RICE with a brake HP greater than or equal to 100 HP and less than 250 HP. Construction/Reconstruction Date = Commenced construction or reconstruction on or after June 12, 2006. Service Type = Normal use. Stationary RICE Type = Compression ignition engine	
C-2521	30 TAC Chapter 115, Storage of VOCs	R5112-1-9	Construction Date = On or after May 12, 1973 Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons Control Device Type = Direct-flame incinerator	
C-2521	30 TAC Chapter 115, Storage of VOCs	R5112-2-4	Construction Date = On or after May 12, 1973 Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons Control Device Type = Direct-flame incinerator	
C-2521	30 TAC Chapter 115, Storage of VOCs	R5112-3-2	Construction Date = On or after May 12, 1973 Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Control Device Type = Direct-flame incinerator	
C-2521	40 CFR Part 60, Subpart Kb	60KB	Product Stored = Waste mixture of indeterminate or variable composition Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
C-253	30 TAC Chapter 115, Storage of VOCs	R5112-1-13	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system True Vapor Pressure = True vapor pressure is greater than or equal to 11 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
C-253	30 TAC Chapter 115, Storage of VOCs	R5112-2-7	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system True Vapor Pressure = True vapor pressure is greater than or equal to 11 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
C-253	30 TAC Chapter 115, Storage of VOCs	R5112-3-5	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system True Vapor Pressure = True vapor pressure is greater than or equal to 11 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
C-253	40 CFR Part 63, Subpart G	63G-1-1	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb. Bypass Lines = Closed vent system has no by-pass lines. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa) Control Device Type = Hazardous waste incinerator as specified in	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
C-253	40 CFR Part 63, Subpart G	63G-2-1	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
C-253	40 CFR Part 63, Subpart G	63G-3-1	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Thermal incinerator</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p> <p>Design Evaluation Submitted = Results of a performance test was submitted to demonstrate compliance with 40 CFR § 63.119(e).</p>	
C-521	30 TAC Chapter 115, Storage of	R5112-1-10	Construction Date = On or after May 12, 1973	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	VOCs		<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-521	30 TAC Chapter 115, Storage of VOCs	R5112-2-5	<p>Construction Date = On or after May 12, 1973</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-521	30 TAC Chapter 115, Storage of VOCs	R5112-3-3	<p>Construction Date = On or after May 12, 1973</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-521	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Waste mixture of indeterminate or variable composition</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p>	
C-521	40 CFR Part 63, Subpart G	63G-1	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>	
C-653	30 TAC Chapter 115, Storage of VOCs	R5112-1-10	<p>Construction Date = On or after May 12, 1973</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-653	30 TAC Chapter 115, Storage of VOCs	R5112-2-5	<p>Construction Date = On or after May 12, 1973</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-653	30 TAC Chapter 115, Storage of VOCs	R5112-3-3	<p>Construction Date = On or after May 12, 1973</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-710	30 TAC Chapter 115, Storage of VOCs	R5112-1-23	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-710	30 TAC Chapter 115, Storage of VOCs	R5112-2-16	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-710	30 TAC Chapter 115, Storage of VOCs	R5112-3-11	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-710	40 CFR Part 63, Subpart G	63G-1-8	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
C-710	40 CFR Part 63, Subpart G	63G-2-8	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
C-710	40 CFR Part 63, Subpart G	63G-3-6	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Thermal incinerator</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p> <p>Design Evaluation Submitted = Results of a performance test was submitted to demonstrate compliance with 40 CFR § 63.119(e).</p>	
C-711	30 TAC Chapter 115, Storage of VOCs	R5112-1-24	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-711	30 TAC Chapter 115, Storage of VOCs	R5112-2-17	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
C-711	30 TAC Chapter 115, Storage of VOCs	R5112-3-12	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
C-711	40 CFR Part 63, Subpart G	63G-1-9	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb. Bypass Lines = Closed vent system has no by-pass lines. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa) Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii) Emission Control Type = Closed vent system (CVS) and control device (fixed roof) Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.	
C-711	40 CFR Part 63, Subpart G	63G-2-9	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb. Bypass Lines = Closed vent system has no by-pass lines. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa) Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
C-711	40 CFR Part 63, Subpart G	63G-3-7	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Thermal incinerator</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p> <p>Design Evaluation Submitted = Results of a performance test was submitted to demonstrate compliance with 40 CFR § 63.119(e).</p>	
C-712A	30 TAC Chapter 115, Storage of VOCs	R5112-1-19	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-712A	30 TAC Chapter 115, Storage of VOCs	R5112-2-12	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
C-712A	30 TAC Chapter 115, Storage of VOCs	R5112-3-8	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-712A	40 CFR Part 63, Subpart G	63G-1-5	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
C-712A	40 CFR Part 63, Subpart G	63G-2-5	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.	
C-712A	40 CFR Part 63, Subpart G	63G-3-3	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Thermal incinerator</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p> <p>Design Evaluation Submitted = Results of a performance test was submitted to demonstrate compliance with 40 CFR § 63.119(e).</p>	
C-712B	30 TAC Chapter 115, Storage of VOCs	R5112-1-20	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-712B	30 TAC Chapter 115, Storage of VOCs	R5112-2-13	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-712B	30 TAC Chapter 115, Storage of VOCs	R5112-3-9	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-712B	40 CFR Part 63, Subpart G	63G-1-6	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
C-712B	40 CFR Part 63, Subpart G	63G-2-6	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
C-712B	40 CFR Part 63,	63G-3-4	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	Subpart G		<p>5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Thermal incinerator</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p> <p>Design Evaluation Submitted = Results of a performance test was submitted to demonstrate compliance with 40 CFR § 63.119(e).</p>	
C-714	30 TAC Chapter 115, Storage of VOCs	R5112-1-25	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-714	30 TAC Chapter 115, Storage of VOCs	R5112-2-18	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-714	30 TAC Chapter 115, Storage of VOCs	R5112-3-13	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-714	40 CFR Part 63, Subpart G	63G-1-10	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
C-714	40 CFR Part 63, Subpart G	63G-2-10	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
C-714	40 CFR Part 63, Subpart G	63G-3-8	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Thermal incinerator</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p> <p>Design Evaluation Submitted = Results of a performance test was submitted to demonstrate compliance with 40 CFR § 63.119(e).</p>	
C-720A	30 TAC Chapter 115, Storage of VOCs	R5112-1-15	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-720A	30 TAC Chapter 115, Storage of VOCs	R5112-1-40	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-720A	30 TAC Chapter 115, Storage of VOCs	R5112-2-29	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
C-720A	30 TAC Chapter 115, Storage of VOCs	R5112-2-8	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-720A	30 TAC Chapter 115, Storage of VOCs	R5112-3-19	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-720A	30 TAC Chapter 115, Storage of VOCs	R5112-3-6	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-720A	40 CFR Part 63, Subpart G	63G-1-2	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.	
C-720A	40 CFR Part 63, Subpart G	63G-1-20	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
C-720A	40 CFR Part 63, Subpart G	63G-2-17	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
C-720A	40 CFR Part 63, Subpart G	63G-2-2	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61,</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
C-720A	40 CFR Part 63, Subpart G	63G-3-10	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Thermal incinerator</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p> <p>Design Evaluation Submitted = Results of a performance test was submitted to demonstrate compliance with 40 CFR § 63.119(e).</p>	
C-720A	40 CFR Part 63, Subpart G	63G-3-2	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Control Device Type = Thermal incinerator</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p> <p>Design Evaluation Submitted = Results of a performance test was submitted to demonstrate compliance with 40 CFR § 63.119(e).</p>	
C-720B	30 TAC Chapter 115, Storage of VOCs	R5112-1-16	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-720B	30 TAC Chapter 115, Storage of VOCs	R5112-1-41	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-720B	30 TAC Chapter 115, Storage of VOCs	R5112-2-30	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
C-720B	30 TAC Chapter 115, Storage of VOCs	R5112-2-9	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a submerged fill pipe and vapor recovery system</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
C-720B	30 TAC Chapter 115, Storage of VOCs	R5112-3-20	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
C-720B	30 TAC Chapter 115, Storage of VOCs	R5112-3-7	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a submerged fill pipe and vapor recovery system True Vapor Pressure = True vapor pressure is greater than or equal to 11 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
C-720B	40 CFR Part 63, Subpart G	63G-1-21	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has no by-pass lines. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii) Emission Control Type = Closed vent system (CVS) and control device (fixed roof) Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.	
C-720B	40 CFR Part 63, Subpart G	63G-1-22	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61,	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
C-720B	40 CFR Part 63, Subpart G	63G-2-16	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
C-720B	40 CFR Part 63, Subpart G	63G-2-18	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			air pollutants by greater than or equal to 90% and less than 95%.	
C-720B	40 CFR Part 63, Subpart G	63G-3-11	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Thermal incinerator</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p> <p>Design Evaluation Submitted = Results of a performance test was submitted to demonstrate compliance with 40 CFR § 63.119(e).</p>	
C-720B	40 CFR Part 63, Subpart G	63G-3-9	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Thermal incinerator</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p> <p>Design Evaluation Submitted = Results of a performance test was submitted to demonstrate compliance with 40 CFR § 63.119(e).</p>	
D-002	40 CFR Part 60, Subpart Ka	60KA	Product Stored = Stored product other than a petroleum liquid	
D-002	40 CFR Part 60, Subpart Kb	60KB	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p>	
D-005	40 CFR Part 60, Subpart Ka	60KA	Product Stored = Petroleum liquid (other than petroleum or condensate)	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Storage Capacity = Capacity is 40,000 gallons (151,416 liters) or less	
D-005	40 CFR Part 60, Subpart Kb	60KB	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
D-006	40 CFR Part 60, Subpart Ka	60KA	Product Stored = Stored product other than a petroleum liquid	
D-006	40 CFR Part 60, Subpart Kb	60KB	Product Stored = Volatile organic liquid Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)	
D-104A	30 TAC Chapter 115, Storage of VOCs	R5112-1-33	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof with slotted sampling and gauge pipes True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons	
D-104A	40 CFR Part 63, Subpart G	63G-1-13	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Seal Type = Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the floating roof NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa) Emission Control Type = Internal floating roof	
D-104B	30 TAC Chapter 115, Storage of VOCs	R5112-1-34	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using an internal floating roof with slotted sampling and gauge pipes True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons	
D-104B	40 CFR Part 63, Subpart G	63G-1-14	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Seal Type = Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>vessel and the edge of the floating roof</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	
D-104C	30 TAC Chapter 115, Storage of VOCs	R5112-1-35	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using an internal floating roof with slotted sampling and gauge pipes</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p>	
D-104C	40 CFR Part 63, Subpart G	63G-1-15	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Seal Type = Two seals mounted one above the other so that each forms a continuous closure that completely covers the space between the wall of the storage vessel and the edge of the floating roof</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is subject to 40 CFR Part 60, Subpart Kb.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Internal floating roof</p>	
D-2525A	30 TAC Chapter 115, Storage of VOCs	R5112-1-29	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
D-2525A	30 TAC Chapter 115, Storage of VOCs	R5112-1-31	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.5 psia</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
D-2525A	30 TAC Chapter 115, Storage of VOCs	R5112-2-21	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
D-2525A	30 TAC Chapter 115, Storage of VOCs	R5112-2-23	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
D-2525A	30 TAC Chapter 115, Storage of VOCs	R5112-3-14	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
D-2525A	30 TAC Chapter 115, Storage of VOCs	R5112-3-16	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
D-2525A	40 CFR Part 63, Subpart G	63G-1-23	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
D-2525A	40 CFR Part 63, Subpart G	63G-2-19	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
D-2525A	40 CFR Part 63, Subpart G	63G-3-12	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Thermal incinerator</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%. Design Evaluation Submitted = Results of a performance test was submitted to demonstrate compliance with 40 CFR § 63.119(e).	
D-2525B	30 TAC Chapter 115, Storage of VOCs	R5112-1-30	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
D-2525B	30 TAC Chapter 115, Storage of VOCs	R5112-1-32	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
D-2525B	30 TAC Chapter 115, Storage of VOCs	R5112-2-22	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
D-2525B	30 TAC Chapter 115, Storage of VOCs	R5112-2-24	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 25,000 gallons Control Device Type = Direct-flame incinerator	
D-2525B	30 TAC Chapter	R5112-3-15	Alternate Control Requirement = Not using an alternate method for demonstrating	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	115, Storage of VOCs		<p>and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
D-2525B	30 TAC Chapter 115, Storage of VOCs	R5112-3-17	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
D-2525B	40 CFR Part 63, Subpart G	63G-1-24	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
D-2525B	40 CFR Part 63, Subpart G	63G-2-20	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
D-2525B	40 CFR Part 63, Subpart G	63G-3-13	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Thermal incinerator</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p> <p>Design Evaluation Submitted = Results of a performance test was submitted to demonstrate compliance with 40 CFR § 63.119(e).</p>	
D-525A	30 TAC Chapter 115, Storage of VOCs	R5112-1-31	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
D-525A	30 TAC Chapter 115, Storage of VOCs	R5112-2-23	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
D-525A	30 TAC Chapter 115, Storage of VOCs	R5112-3-16	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
D-525A	40 CFR Part 63, Subpart G	63G-1-25	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
D-525A	40 CFR Part 63, Subpart G	63G-2-21	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60,</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
D-525A	40 CFR Part 63, Subpart G	63G-3-14	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Thermal incinerator</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p> <p>Design Evaluation Submitted = Results of a performance test was submitted to demonstrate compliance with 40 CFR § 63.119(e).</p>	
D-525B	30 TAC Chapter 115, Storage of VOCs	R5112-1-32	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
D-525B	30 TAC Chapter 115, Storage of VOCs	R5112-2-24	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
D-525B	30 TAC Chapter 115, Storage of VOCs	R5112-3-17	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
D-525B	40 CFR Part 63, Subpart G	63G-1-26	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
D-525B	40 CFR Part 63, Subpart G	63G-2-22	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60,</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Hazardous waste incinerator as specified in 40 CFR § 63.120(d)(8)(iii)</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p>	
D-525B	40 CFR Part 63, Subpart G	63G-3-15	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is less than 11.11 psi (76.6 kPa)</p> <p>Control Device Type = Thermal incinerator</p> <p>Emission Control Type = Closed vent system (CVS) and control device (fixed roof)</p> <p>Control Device Design = The control device was not installed on or before December 31, 1992 or was not designed to reduce inlet emissions of total organic hazardous air pollutants by greater than or equal to 90% and less than 95%.</p> <p>Design Evaluation Submitted = Results of a performance test was submitted to demonstrate compliance with 40 CFR § 63.119(e).</p>	
D-540	30 TAC Chapter 115, Storage of VOCs	R5112-1-7	<p>Construction Date = On or after May 12, 1973</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
D-540	30 TAC Chapter 115, Storage of	R5112-2-2	Construction Date = On or after May 12, 1973	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	VOCs		<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
D-540	30 TAC Chapter 115, Storage of VOCs	R5112-3-1	<p>Construction Date = On or after May 12, 1973</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia but less than 11 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p> <p>Control Device Type = Direct-flame incinerator</p>	
D-540	40 CFR Part 60, Subpart Kb	60Kb	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p>	
D-750	40 CFR Part 60, Subpart Ka	60KA	Product Stored = Stored product other than a petroleum liquid	
D-750	40 CFR Part 60, Subpart Kb	60Kb	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p>	
D-751	40 CFR Part 60, Subpart Ka	60KA	Product Stored = Stored product other than a petroleum liquid	
D-751	40 CFR Part 60, Subpart Kb	60Kb	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p>	
LVPTRANSFER	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-0	<p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure is less than 1.5 psia.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
MOTOR1	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-20	Chapter 115 Facility Type = Motor vehicle fuel dispensing facility	
VCMHE	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-12	<p>Chapter 115 Control Device Type = Vapor control system with a direct flame incinerator.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
VCMHE	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-17	<p>Chapter 115 Control Device Type = Vapor control system with a direct flame incinerator.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
VCMHE	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-5	<p>Chapter 115 Control Device Type = Vapor control system with a direct flame incinerator.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
VCMHE	40 CFR Part 63, Subpart G	63G-12	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Incinerator other than a catalytic incinerator.</p> <p>Halogenated Emissions = There are halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Combustion Device = Halogenated emission streams from the Group 1 transfer rack are combusted.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Emission Rate = The vent stream halogen atom mass emission rate is not being reduced to less than 0.45 kilograms per hour prior to any combustion control device.</p> <p>Performance Test Exemption = Boiler, process heater, or incinerator does not qualify for exemption and a performance test is required.</p> <p>Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H.</p> <p>Installation Date = The installation date of the halogen reduction device was on or after December 31, 1992.</p> <p>Shared Control Device = The control device is shared between transfer racks and process vents.</p> <p>Multiple Arms = Control device is shared between multiple arms loading simultaneously.</p> <p>Scrubber = A scrubber is being used to reduce the halogenated vent stream.</p>	
VCMHE	40 CFR Part 63, Subpart G	63G-3	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Incinerator other than a catalytic incinerator.</p> <p>Halogenated Emissions = There are halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Combustion Device = Halogenated emission streams from the Group 1 transfer rack are combusted.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Emission Rate = The vent stream halogen atom mass emission rate is not being reduced to less than 0.45 kilograms per hour prior to any combustion control device.</p> <p>Performance Test Exemption = The incinerator is burning hazardous waste and meets the requirements of 40 CFR § 63.128(c)(7).</p> <p>Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H.</p> <p>Installation Date = The installation date of the halogen reduction device was prior to December 31, 1992.</p> <p>Shared Control Device = The control device is shared between transfer racks and process vents.</p> <p>Multiple Arms = Control device is shared between multiple arms loading simultaneously.</p> <p>Scrubber = A scrubber is being used to reduce the halogenated vent stream.</p>	
VCMHE	40 CFR Part 63, Subpart G	63G-8	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Incinerator other than a catalytic incinerator.</p> <p>Halogenated Emissions = There are halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Combustion Device = Halogenated emission streams from the Group 1 transfer rack are combusted.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Emission Rate = The vent stream halogen atom mass emission rate is not being reduced to less than 0.45 kilograms per hour prior to any combustion control device.</p> <p>Performance Test Exemption = The incinerator is burning hazardous waste and meets the requirements of 40 CFR § 63.128(c)(7).</p> <p>Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H.</p> <p>Installation Date = The installation date of the halogen reduction device was prior to December 31, 1992.</p> <p>Shared Control Device = The control device is shared between transfer racks and process vents.</p> <p>Multiple Arms = Control device is shared between multiple arms loading simultaneously.</p> <p>Scrubber = A scrubber is being used to reduce the halogenated vent stream.</p>	
VCMLE	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-13	<p>Chapter 115 Control Device Type = Vapor control system with a direct flame incinerator.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
VCMLE	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-18	<p>Chapter 115 Control Device Type = Vapor control system with a direct flame incinerator.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
VCMLE	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-6	<p>Chapter 115 Control Device Type = Vapor control system with a direct flame incinerator.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
VCMLE	40 CFR Part 63, Subpart G	63G-13	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Incinerator other than a catalytic incinerator.</p> <p>Halogenated Emissions = There are halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Combustion Device = Halogenated emission streams from the Group 1 transfer rack are combusted.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Emission Rate = The vent stream halogen atom mass emission rate is not being reduced to less than 0.45 kilograms per hour prior to any combustion control device.</p> <p>Performance Test Exemption = Boiler, process heater, or incinerator does not qualify for exemption and a performance test is required.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H.</p> <p>Installation Date = The installation date of the halogen reduction device was on or after December 31, 1992.</p> <p>Shared Control Device = The control device is shared between transfer racks and process vents.</p> <p>Multiple Arms = Control device is shared between multiple arms loading simultaneously.</p> <p>Scrubber = A scrubber is being used to reduce the halogenated vent stream.</p>	
VCMLE	40 CFR Part 63, Subpart G	63G-4	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Incinerator other than a catalytic incinerator.</p> <p>Halogenated Emissions = There are halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Combustion Device = Halogenated emission streams from the Group 1 transfer rack are combusted.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Emission Rate = The vent stream halogen atom mass emission rate is not being reduced to less than 0.45 kilograms per hour prior to any combustion control device.</p> <p>Performance Test Exemption = The incinerator is burning hazardous waste and meets the requirements of 40 CFR § 63.128(c)(7).</p> <p>Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H.</p> <p>Installation Date = The installation date of the halogen reduction device was prior to December 31, 1992.</p> <p>Shared Control Device = The control device is shared between transfer racks and process vents.</p> <p>Multiple Arms = Control device is shared between multiple arms loading simultaneously.</p> <p>Scrubber = A scrubber is being used to reduce the halogenated vent stream.</p>	
VCMLE	40 CFR Part 63, Subpart G	63G-9	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Incinerator other than a catalytic incinerator.</p> <p>Halogenated Emissions = There are halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Combustion Device = Halogenated emission streams from the Group 1 transfer rack are combusted.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Emission Rate = The vent stream halogen atom mass emission rate is not being reduced to less than 0.45 kilograms per hour prior to any combustion control device.</p> <p>Performance Test Exemption = The incinerator is burning hazardous waste and meets the requirements of 40 CFR § 63.128(c)(7).</p> <p>Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H.</p> <p>Installation Date = The installation date of the halogen reduction device was prior to December 31, 1992.</p> <p>Shared Control Device = The control device is shared between transfer racks and process vents.</p> <p>Multiple Arms = Control device is shared between multiple arms loading simultaneously.</p> <p>Scrubber = A scrubber is being used to reduce the halogenated vent stream.</p>	
VCMML	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-14	<p>Chapter 115 Control Device Type = Vapor control system with a direct flame incinerator.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Control Options = Vapor control system that maintains a control efficiency of at least 90%.	
VCMML	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-19	<p>Chapter 115 Control Device Type = Vapor control system with a direct flame incinerator.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
VCMML	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-7	<p>Chapter 115 Control Device Type = Vapor control system with a direct flame incinerator.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
VCMML	40 CFR Part 63, Subpart G	63G-10	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Incinerator other than a catalytic incinerator.</p> <p>Halogenated Emissions = There are halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>emissions of organic hazardous air pollutants.</p> <p>Combustion Device = Halogenated emission streams from the Group 1 transfer rack are combusted.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Emission Rate = The vent stream halogen atom mass emission rate is not being reduced to less than 0.45 kilograms per hour prior to any combustion control device.</p> <p>Performance Test Exemption = The incinerator is burning hazardous waste and meets the requirements of 40 CFR § 63.128(c)(7).</p> <p>Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H.</p> <p>Installation Date = The installation date of the halogen reduction device was prior to December 31, 1992.</p> <p>Shared Control Device = The control device is shared between transfer racks and process vents.</p> <p>Multiple Arms = Control device is shared between multiple arms loading simultaneously.</p> <p>Scrubber = A scrubber is being used to reduce the halogenated vent stream.</p>	
VCMML	40 CFR Part 63, Subpart G	63G-14	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Incinerator other than a catalytic incinerator.</p> <p>Halogenated Emissions = There are halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Combustion Device = Halogenated emission streams from the Group 1 transfer rack are combusted.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Emission Rate = The vent stream halogen atom mass emission rate is not being reduced to less than 0.45 kilograms per hour prior to any combustion control device.</p> <p>Performance Test Exemption = Boiler, process heater, or incinerator does not qualify for exemption and a performance test is required.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H.</p> <p>Installation Date = The installation date of the halogen reduction device was on or after December 31, 1992.</p> <p>Shared Control Device = The control device is shared between transfer racks and process vents.</p> <p>Multiple Arms = Control device is shared between multiple arms loading simultaneously.</p> <p>Scrubber = A scrubber is being used to reduce the halogenated vent stream.</p>	
VCMML	40 CFR Part 63, Subpart G	63G-5	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Incinerator other than a catalytic incinerator.</p> <p>Halogenated Emissions = There are halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Combustion Device = Halogenated emission streams from the Group 1 transfer rack are combusted.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Emission Rate = The vent stream halogen atom mass emission rate is not being reduced to less than 0.45 kilograms per hour prior to any combustion control device.</p> <p>Performance Test Exemption = The incinerator is burning hazardous waste and meets the requirements of 40 CFR § 63.128(c)(7).</p> <p>Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H.</p> <p>Installation Date = The installation date of the halogen reduction device was prior to December 31, 1992.</p> <p>Shared Control Device = The control device is shared between transfer racks and process vents.</p> <p>Multiple Arms = Control device is shared between multiple arms loading simultaneously.</p> <p>Scrubber = A scrubber is being used to reduce the halogenated vent stream.</p>	
VCMRAIL	30 TAC Chapter 115, Loading	R5211-11	Chapter 115 Control Device Type = Vapor control system with a direct flame incinerator.	Related Standard - Removed 115.214(b)(1)(C) since the unit is a railcar,

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
	and Unloading of VOC		<p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	and does not qualify as a "tank truck" per 115.10(42) & (43)
VCMAIL	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-16	<p>Chapter 115 Control Device Type = Vapor control system with a direct flame incinerator.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	Related Standard - Removed 115.214(b)(1)(C) since the unit is a railcar, and does not qualify as a "tank truck" per 115.10(42) & (43)
VCMAIL	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-4	<p>Chapter 115 Control Device Type = Vapor control system with a direct flame incinerator.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p>	Related Standard - Removed 115.214(b)(1)(C) since the unit is a railcar, and does not qualify as a "tank truck" per 115.10(42) & (43)

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>	
VCMRAIL	40 CFR Part 63, Subpart G	63G-11	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Incinerator other than a catalytic incinerator.</p> <p>Halogenated Emissions = There are halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Combustion Device = Halogenated emission streams from the Group 1 transfer rack are combusted.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Emission Rate = The vent stream halogen atom mass emission rate is not being reduced to less than 0.45 kilograms per hour prior to any combustion control device.</p> <p>Performance Test Exemption = Boiler, process heater, or incinerator does not qualify for exemption and a performance test is required.</p> <p>Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H.</p> <p>Installation Date = The installation date of the halogen reduction device was on or after December 31, 1992.</p> <p>Shared Control Device = The control device is shared between transfer racks and process vents.</p> <p>Multiple Arms = Control device is shared between multiple arms loading simultaneously.</p> <p>Scrubber = A scrubber is being used to reduce the halogenated vent stream.</p>	
VCMRAIL	40 CFR Part 63, Subpart G	63G-2	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Incinerator other than a catalytic incinerator.</p> <p>Halogenated Emissions = There are halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>emissions of organic hazardous air pollutants.</p> <p>Combustion Device = Halogenated emission streams from the Group 1 transfer rack are combusted.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Emission Rate = The vent stream halogen atom mass emission rate is not being reduced to less than 0.45 kilograms per hour prior to any combustion control device.</p> <p>Performance Test Exemption = The incinerator is burning hazardous waste and meets the requirements of 40 CFR § 63.128(c)(7).</p> <p>Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H.</p> <p>Installation Date = The installation date of the halogen reduction device was prior to December 31, 1992.</p> <p>Shared Control Device = The control device is shared between transfer racks and process vents.</p> <p>Multiple Arms = Control device is shared between multiple arms loading simultaneously.</p> <p>Scrubber = A scrubber is being used to reduce the halogenated vent stream.</p>	
VCMAIL	40 CFR Part 63, Subpart G	63G-7	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Incinerator other than a catalytic incinerator.</p> <p>Halogenated Emissions = There are halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Combustion Device = Halogenated emission streams from the Group 1 transfer rack are combusted.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Emission Rate = The vent stream halogen atom mass emission rate is not being reduced to less than 0.45 kilograms per hour prior to any combustion control device.</p> <p>Performance Test Exemption = The incinerator is burning hazardous waste and meets the requirements of 40 CFR § 63.128(c)(7).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Title 40 § 63.128(h) Option = The transfer rack is complying with 40 CFR § 63.128(a) or (b).</p> <p>Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H.</p> <p>Installation Date = The installation date of the halogen reduction device was prior to December 31, 1992.</p> <p>Shared Control Device = The control device is shared between transfer racks and process vents.</p> <p>Multiple Arms = Control device is shared between multiple arms loading simultaneously.</p> <p>Scrubber = A scrubber is being used to reduce the halogenated vent stream.</p>	
VCMSHIP	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-10	<p>Chapter 115 Control Device Type = Vapor control system with a direct flame incinerator.</p> <p>Chapter 115 Facility Type = Marine terminal</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Marine Terminal Exemptions = The marine terminal is not claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B).</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor balance system.</p>	
VCMSHIP	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-15	<p>Chapter 115 Control Device Type = Vapor control system with a direct flame incinerator.</p> <p>Chapter 115 Facility Type = Marine terminal</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Marine Terminal Exemptions = The marine terminal is not claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B).</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Control Options = Vapor balance system.	
VCMSHIP	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-3	<p>Chapter 115 Control Device Type = Vapor control system with a direct flame incinerator.</p> <p>Chapter 115 Facility Type = Marine terminal</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas, crude oil, condensate and gasoline.</p> <p>Marine Terminal Exemptions = The marine terminal is not claiming one or more of the exemptions in 30 TAC § 115.217(a)(5)(B).</p> <p>Transfer Type = Only loading.</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor balance system.</p>	
VCMSHIP	40 CFR Part 63, Subpart Y	63Y-2	<p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.</p> <p>Vapor Pressure = Vapor pressure is greater than or equal to 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p> <p>Subpart BB Applicability = Marine vessel loading operations are not subject to and complying with 40 CFR Part 61, Subpart BB.</p> <p>Material Loaded = Material other than crude oil or gasoline.</p> <p>HAP Impurities Only = Marine vessel loading operations at loading berths transfer liquids containing organic hazardous air pollutants other than as impurities.</p> <p>Source Emissions = Source with emissions less than 10 and 25 tons.</p>	
VCMSHIP	40 CFR Part 63, Subpart Y	63Y-4	<p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.</p> <p>Vapor Pressure = Vapor pressure is greater than or equal to 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p> <p>Subpart BB Applicability = Marine vessel loading operations are not subject to and complying with 40 CFR Part 61, Subpart BB.</p> <p>Material Loaded = Material other than crude oil or gasoline.</p> <p>HAP Impurities Only = Marine vessel loading operations at loading berths transfer liquids containing organic hazardous air pollutants other than as impurities.</p> <p>Source Emissions = Source with emissions less than 10 and 25 tons.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
VCMSHIP	40 CFR Part 63, Subpart Y	63Y-5	<p>Subpart Y Facility Type = Existing onshore loading terminal (located onshore or less than 0.5 miles from shore).</p> <p>Ballasting Operations = Operations other than or in addition to ballasting operations are performed at the facility.</p> <p>Vapor Pressure = Vapor pressure is greater than or equal to 10.3 kilopascals (1.5 psia) at standard conditions, 20° C and 760 mm Hg.</p> <p>Subpart BB Applicability = Marine vessel loading operations are not subject to and complying with 40 CFR Part 61, Subpart BB.</p> <p>Material Loaded = Material other than crude oil or gasoline.</p> <p>HAP Impurities Only = Marine vessel loading operations at loading berths transfer liquids containing organic hazardous air pollutants other than as impurities.</p> <p>Source Emissions = Source with emissions less than 10 and 25 tons.</p>	
GRPFURN-5D	40 CFR Part 63, Subpart DDDDD	63DDDDDD	CONSTRUCTION/RECONSTRUCTION DATE = Construction or reconstruction began after June 4, 2010.	
GRPINCIN	40 CFR Part 63, Subpart EEE	63EEEE-HAP	<p>Baghouse = The furnace is not equipped with a baghouse.</p> <p>Existing Source = The furnace is an existing source (construction or reconstruction commenced on or before April 20, 2004).</p> <p>Area Source = The furnace is a major source as defined under § 63.2.</p> <p>Dioxin-Listed = The furnace does not burn the dioxin-listed hazardous wastes F020, F021, F022, F023, F026, or F027.</p> <p>Dioxin/Furan Standard = Complying with the CO standard in § 63.1218(a)(1) or (b)(1).</p> <p>DRE Previous Test = DRE testing during the comprehensive initial performance testing is used to document conformance with the DRE standard.</p> <p>CO/THC Standard = Complying with the CO standard in § 63.1218(a)(5)(i) or (b)(5)(i).</p> <p>Feed Zone = The source feeds waste at the normal flame zone.</p> <p>TOT-Cl Standard = Complying with the 25 ppmv standard in § 63.1218(a)(6)(i) or (b)(6)(i).</p>	
VCM-1	40 CFR Part 63, Subpart EEE	63EEEE-HAP	<p>Baghouse = The furnace is not equipped with a baghouse.</p> <p>Existing Source = The furnace is an existing source (construction or reconstruction commenced on or before April 20, 2004).</p> <p>Area Source = The furnace is a major source as defined under § 63.2.</p> <p>Dioxin-Listed = The furnace does not burn the dioxin-listed hazardous wastes F020, F021, F022, F023, F026, or F027.</p> <p>Dioxin/Furan Standard = Complying with the CO standard in § 63.1218(a)(1) or (b)(1).</p> <p>DRE Previous Test = DRE testing during the comprehensive initial performance testing is used to document conformance with the DRE standard.</p> <p>CO/THC Standard = Complying with the CO standard in § 63.1218(a)(5)(i) or (b)(5)(i).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Feed Zone = The source feeds waste at the normal flame zone.</p> <p>TOT-Cl Standard = Complying with the 25 ppmv standard in § 63.1218(a)(6)(i) or (b)(6)(i).</p>	
VCM-2	40 CFR Part 63, Subpart EEE	63EEE-HAP	<p>Baghouse = The furnace is not equipped with a baghouse.</p> <p>Existing Source = The furnace is an existing source (construction or reconstruction commenced on or before April 20, 2004).</p> <p>Area Source = The furnace is a major source as defined under § 63.2.</p> <p>Dioxin-Listed = The furnace does not burn the dioxin-listed hazardous wastes F020, F021, F022, F023, F026, or F027.</p> <p>Dioxin/Furan Standard = Complying with the CO standard in § 63.1218(a)(1) or (b)(1).</p> <p>DRE Previous Test = DRE testing during the comprehensive initial performance testing is used to document conformance with the DRE standard.</p> <p>CO/THC Standard = Complying with the CO standard in § 63.1218(a)(5)(i) or (b)(5)(i).</p> <p>Feed Zone = The source feeds waste at the normal flame zone.</p> <p>TOT-Cl Standard = Complying with the 25 ppmv standard in § 63.1218(a)(6)(i) or (b)(6)(i).</p>	
DB-1	40 CFR Part 60, Subpart Db	60DB-3	<p>Construction/Modification Date = Constructed or reconstructed after July 9, 1997, and on or before February 28, 2005.</p> <p>D-Series Fuel Type #1 = Natural gas.</p> <p>D-Series Fuel Type #2 = Nonsolid non fossil fuel other than nonsolid byproduct/waste or hazardous waste.</p> <p>Heat Input Capacity = Heat input capacity is greater than 250 MMBtu/hr (73 MW).</p> <p>PM Monitoring Type = No particulate monitoring.</p> <p>Opacity Monitoring Type = No particulate (opacity) monitoring.</p> <p>Subpart Da = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart Da.</p> <p>Changes to Existing Affected Facility = No change has been made to the existing steam generating unit, which was not previously subject to 40 CFR Part 60, Subpart Db, for the sole purpose of combusting gases containing totally reduced sulfur as defined under 40 CFR § 60.281.</p> <p>NOx Monitoring Type = Continuous emission monitoring system.</p> <p>Subpart D = The affected facility does not meet the applicability requirements of 40 CFR Part 60, Subpart D.</p> <p>Electrical or Mechanical Output = More than 10% of the annual output is electrical or mechanical.</p> <p>SO2 Monitoring Type = Fuel certification (maintaining receipts per § 60.49b(r)(1)).</p> <p>Subpart Ea, Eb or AAAA = The affected facility does not meet applicability requirements of and is subject to 40 CFR Part 60, Subpart Ea, Eb or AAAA.</p> <p>Subpart J = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart J.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Output Based Limit = The facility is not electing to comply with the output based limit in § 60.44b(l)(3).</p> <p>Subpart E = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart E.</p> <p>Subpart KKKK = The affected facility is not a heat recovery steam generator associated with combined cycle gas turbines and that meets applicability requirements of and is subject to 40 CFR Part 60, Subpart KKKK.</p> <p>Technology Type = None.</p> <p>ACF Option - SO₂ = Other ACF or no ACF.</p> <p>Subpart Cb or BBBB = The affected facility is not covered by an EPA approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart Cb or BBBB emission guidelines.</p> <p>Unit Type = Duct burner as part of combined cycle system (compliance with NO_x limitations is determined by conducting a performance test).</p> <p>ACF Option - PM = Other ACF or no ACF.</p> <p>ACF Option - NO_x = Other ACF or no ACF.</p>	
DB-1	40 CFR Part 60, Subpart Dc	60DC	<p>Construction/Modification Date = After June 9, 1989 but on or before February 28, 2005.</p> <p>Maximum Design Heat Input Capacity = Maximum design heat input capacity is greater than 100 MMBtu/hr (29 MW).</p>	
DB-2	40 CFR Part 60, Subpart Db	60DB-4	<p>Alternate Emission Limit (AEL) = The facility combusts byproduct/waste with either natural gas or oil and did not petition the EPA Administrator to establish a NO_x emission limit that applies specifically when the byproduct/waste is combusted.</p> <p>Construction/Modification Date = Constructed or reconstructed after July 9, 1997, and on or before February 28, 2005.</p> <p>D-Series Fuel Type #1 = Natural gas.</p> <p>D-Series Fuel Type #2 = Nonsolid non fossil fuel other than nonsolid byproduct/waste or hazardous waste.</p> <p>Heat Input Capacity = Heat input capacity is greater than 250 MMBtu/hr (73 MW).</p> <p>PM Monitoring Type = No particulate monitoring.</p> <p>Opacity Monitoring Type = No particulate (opacity) monitoring.</p> <p>Subpart Da = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart Da.</p> <p>Changes to Existing Affected Facility = No change has been made to the existing steam generating unit, which was not previously subject to 40 CFR Part 60, Subpart Db, for the sole purpose of combusting gases containing totally reduced sulfur as defined under 40 CFR § 60.281.</p> <p>NO_x Monitoring Type = Continuous emission monitoring system.</p> <p>Subpart D = The affected facility does not meet the applicability requirements of 40 CFR Part 60, Subpart D.</p> <p>Electrical or Mechanical Output = More than 10% of the annual output is electrical or mechanical.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>SO2 Monitoring Type = Fuel certification (maintaining receipts per § 60.49b(r)(1)).</p> <p>Subpart Ea, Eb or AAAA = The affected facility does not meet applicability requirements of and is subject to 40 CFR Part 60, Subpart Ea, Eb or AAAA.</p> <p>Subpart J = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart J.</p> <p>Output Based Limit = The facility is not electing to comply with the output based limit in § 60.44b(l)(3).</p> <p>Subpart E = The affected facility does not meet applicability requirements of 40 CFR Part 60, Subpart E.</p> <p>Subpart KKKK = The affected facility is not a heat recovery steam generator associated with combined cycle gas turbines and that meets applicability requirements of and is subject to 40 CFR Part 60, Subpart KKKK.</p> <p>Technology Type = None.</p> <p>ACF Option - SO2 = Other ACF or no ACF.</p> <p>Subpart Cb or BBBB = The affected facility is not covered by an EPA approved State or Federal section 111(d)/129 plan implementing 40 CFR Part 60, Subpart Cb or BBBB emission guidelines.</p> <p>Unit Type = Duct burner as part of combined cycle system (compliance with NO_x limitations is determined by conducting a performance test).</p> <p>ACF Option - PM = Other ACF or no ACF.</p> <p>ACF Option - NOx = Other ACF or no ACF.</p>	
UNIT 1	40 CFR Part 60, Subpart GG	60GG-1	<p>Duct Burner = The turbine is part of a combined cycle turbine system equipped with supplemental heat (duct burner).</p> <p>Peak Load Heat Input = Heat Input is greater than 100 MMBtu/hr (107.2 GJ/hr)</p> <p>Construction/Modification Date = On or after October 3, 1982 and before July 8, 2004.</p> <p>NOx Allowance = The owner or operator is not electing to use a NO_x allowance in determining emission limits in 40 CFR § 60.332(a).</p> <p>Sulfur Content = Compliance is demonstrated by determining the sulfur content of the fuel.</p> <p>Turbine Cycle = Unit recovers heat from the gas turbine exhaust to heat water or generate steam.</p> <p>Fuel Type Fired = Natural gas meeting the definition in § 60.331(u).</p> <p>Subpart GG Service Type = Type of service other than research and development, emergency, military or electrical utility generation.</p> <p>Fuel Supply = Stationary gas turbine is supplied its fuel without intermediate bulk storage.</p> <p>Fuel Monitoring Schedule = Previously approved custom fuel monitoring schedule.</p> <p>Manufacturer's Rated Base Load = Base load is greater than 30 MW.</p>	
UNIT 1	40 CFR Part 63, Subpart YYYY	63YYYY	<p>Construction/Reconstruction Date = Turbine was constructed, modified or reconstructed after 1/14/2003.</p> <p>Rate Peak Power Output = Power output rating is one megawatt or greater.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Type of Service = Turbine is used in non-emergency service. Fuel Fired = Turbine is fired with natural gas.	
UNIT 2	40 CFR Part 60, Subpart GG	60GG-2	Duct Burner = The turbine is part of a combined cycle turbine system equipped with supplemental heat (duct burner). NO _x Control Method = NO _x control method other than water or steam injection or selective catalytic reduction. Peak Load Heat Input = Heat Input is greater than 100 MMBtu/hr (107.2 GJ/hr) Construction/Modification Date = On or after October 3, 1982 and before July 8, 2004. NO _x Allowance = The owner or operator is not electing to use a NO _x allowance in determining emission limits in 40 CFR § 60.332(a). NO _x Monitoring Method = Continuous emission monitoring system. Sulfur Content = Compliance is demonstrated by determining the sulfur content of the fuel. Turbine Cycle = Unit recovers heat from the gas turbine exhaust to heat water or generate steam. Fuel Type Fired = Natural gas meeting the definition in § 60.331(u). Subpart GG Service Type = Type of service other than research and development, emergency, military or electrical utility generation. Fuel Supply = Stationary gas turbine is supplied its fuel without intermediate bulk storage. Fuel Monitoring Schedule = Previously approved custom fuel monitoring schedule. Manufacturer's Rated Base Load = Base load is greater than 30 MW.	
UNIT 2	40 CFR Part 63, Subpart YYYY	63YYYY	Construction/Reconstruction Date = Turbine was constructed, modified or reconstructed after 1/14/2003. Rate Peak Power Output = Power output rating is one megawatt or greater. Type of Service = Turbine is used in non-emergency service. Fuel Fired = Turbine is fired with natural gas.	
EDC-7	40 CFR Part 63, Subpart H	63H-ALL-EDC-1	ANY (CLOSED VENT SYSTEMS) = COMPONENT PRESENT ANY (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT BYPASS LINES = FUGITIVE UNIT WITH A CLOSED-VENT SYSTEM DOES NOT CONTAIN A BY-PASS LINE THAT COULD DIVERT A VENT STREAM AWAY FROM THE CONTROL DEVICE AND TO THE ATMOSPHERE EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE GAS/VAPOR OR LIGHT LIQUID SERVICE (AGITATORS) = COMPONENT PRESENT LIGHT LIQUID SERVICE (PUMPS) = COMPONENT PRESENT HEAVY LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT HEAVY LIQUID SERVICE (OPEN-ENDED VALVES OR LINES) = COMPONENT NOT	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>PRESENT</p> <p>HEAVY LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT</p> <p>NON RESEARCH AND DEVELOPMENT/BATCH PROCESSES = FUGITIVE UNIT CONTAINS PROCESSES OTHER THAN RESEARCH AND DEVELOPMENT FACILITIES AND BENCH-SCALE BATCH PROCESSES</p> <p>RECOVERY OR RECAPTURE DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>UNSAFE TO INSPECT = FOR A FUGITIVE UNIT THAT CONTAINS ANY CLOSED-VENT SYSTEM, THERE ARE NO PARTS DESIGNATED AS UNSAFE TO INSPECT</p> <p>ANY (INSTRUMENTATION SYSTEMS) = COMPONENT PRESENT</p> <p>DIFFICULT TO INSPECT = FUGITIVE UNIT CONTAINS ANY CLOSED-VENT SYSTEM WITH PARTS DESIGNATED AS DIFFICULT TO INSPECT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (VALVES) = COMPONENT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR PUMPS</p> <p>VACUUM SERVICE = NOT ALL OF THE EQUIPMENT IN THE FUGITIVE UNIT IS IN VACUUM SERVICE</p> <p>ANY (COMPRESSORS) = COMPONENT PRESENT</p> <p>ENCLOSED COMBUSTION DEVICES (CLOSED VENT SYSTEMS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (VALVES) = COMPONENT NOT PRESENT</p> <p>LESS THAN 300 OPERATING HOURS = THE FUGITIVE UNIT DOES NOT CONTAIN ANY EQUIPMENT IN ORGANIC HAZARDOUS AIR POLLUTANT (HAP) SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR</p> <p>ANY (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT PRESENT</p> <p>GAS VAPOR SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR VALVES</p> <p>AMEL = FUGITIVE UNIT SOURCE OWNER/OPERATOR IS NOT ELECTING TO COMPLY WITH AN ALTERNATIVE MEANS OF EMISSION LIMITATION (AMEL)</p> <p>FLARES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT</p> <p>LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (CONNECTORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT NOT PRESENT</p> <p>ANY (SAMPLING CONNECTION SYSTEMS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (SAMPLING CONNECTION SYSTEMS) = COMPONENT NOT</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			PRESENT	
EDC-7	40 CFR Part 63, Subpart H	63H-ALL-EDC-2	<p>ANY (CLOSED VENT SYSTEMS) = COMPONENT PRESENT</p> <p>ANY (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p> <p>BYPASS LINES = FUGITIVE UNIT WITH A CLOSED-VENT SYSTEM DOES NOT CONTAIN A BY-PASS LINE THAT COULD DIVERT A VENT STREAM AWAY FROM THE CONTROL DEVICE AND TO THE ATMOSPHERE</p> <p>EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (AGITATORS) = COMPONENT PRESENT</p> <p>LIGHT LIQUID SERVICE (PUMPS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (OPEN-ENDED VALVES OR LINES) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT</p> <p>NON RESEARCH AND DEVELOPMENT/BATCH PROCESSES = FUGITIVE UNIT CONTAINS PROCESSES OTHER THAN RESEARCH AND DEVELOPMENT FACILITIES AND BENCH-SCALE BATCH PROCESSES</p> <p>RECOVERY OR RECAPTURE DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>UNSAFE TO INSPECT = FOR A FUGITIVE UNIT THAT CONTAINS ANY CLOSED-VENT SYSTEM, THERE ARE NO PARTS DESIGNATED AS UNSAFE TO INSPECT</p> <p>ANY (INSTRUMENTATION SYSTEMS) = COMPONENT PRESENT</p> <p>DIFFICULT TO INSPECT = FUGITIVE UNIT CONTAINS ANY CLOSED-VENT SYSTEM WITH PARTS DESIGNATED AS DIFFICULT TO INSPECT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (VALVES) = COMPONENT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR PUMPS</p> <p>VACUUM SERVICE = NOT ALL OF THE EQUIPMENT IN THE FUGITIVE UNIT IS IN VACUUM SERVICE</p> <p>ANY (COMPRESSORS) = COMPONENT PRESENT</p> <p>ENCLOSED COMBUSTION DEVICES (CLOSED VENT SYSTEMS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (VALVES) = COMPONENT NOT PRESENT</p> <p>LESS THAN 300 OPERATING HOURS = THE FUGITIVE UNIT DOES NOT CONTAIN ANY EQUIPMENT IN ORGANIC HAZARDOUS AIR POLLUTANT (HAP) SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR</p> <p>ANY (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT PRESENT</p> <p>GAS VAPOR SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>PROGRAM FOR VALVES</p> <p>AMEL = FUGITIVE UNIT SOURCE OWNER/OPERATOR IS NOT ELECTING TO COMPLY WITH AN ALTERNATIVE MEANS OF EMISSION LIMITATION (AMEL)</p> <p>FLARES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT</p> <p>LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (CONNECTORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT NOT PRESENT</p> <p>ANY (SAMPLING CONNECTION SYSTEMS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (SAMPLING CONNECTION SYSTEMS) = COMPONENT NOT PRESENT</p>	
VCM-9	40 CFR Part 63, Subpart H	63H-ALL-VCM-1	<p>ANY (CLOSED VENT SYSTEMS) = COMPONENT PRESENT</p> <p>ANY (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p> <p>BYPASS LINES = FUGITIVE UNIT WITH A CLOSED-VENT SYSTEM DOES NOT CONTAIN A BY-PASS LINE THAT COULD DIVERT A VENT STREAM AWAY FROM THE CONTROL DEVICE AND TO THE ATMOSPHERE</p> <p>EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (AGITATORS) = COMPONENT PRESENT</p> <p>LIGHT LIQUID SERVICE (PUMPS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (OPEN-ENDED VALVES OR LINES) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT</p> <p>NON RESEARCH AND DEVELOPMENT/BATCH PROCESSES = FUGITIVE UNIT CONTAINS PROCESSES OTHER THAN RESEARCH AND DEVELOPMENT FACILITIES AND BENCH-SCALE BATCH PROCESSES</p> <p>RECOVERY OR RECAPTURE DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>UNSAFE TO INSPECT = FOR A FUGITIVE UNIT THAT CONTAINS ANY CLOSED-VENT SYSTEM, THERE ARE NO PARTS DESIGNATED AS UNSAFE TO INSPECT</p> <p>ANY (INSTRUMENTATION SYSTEMS) = COMPONENT PRESENT</p> <p>DIFFICULT TO INSPECT = FUGITIVE UNIT CONTAINS ANY CLOSED-VENT SYSTEM WITH PARTS DESIGNATED AS DIFFICULT TO INSPECT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (VALVES) = COMPONENT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR PUMPS</p> <p>VACUUM SERVICE = NOT ALL OF THE EQUIPMENT IN THE FUGITIVE UNIT IS IN</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>VACUUM SERVICE</p> <p>ANY (COMPRESSORS) = COMPONENT PRESENT</p> <p>ENCLOSED COMBUSTION DEVICES (CLOSED VENT SYSTEMS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (VALVES) = COMPONENT NOT PRESENT</p> <p>LESS THAN 300 OPERATING HOURS = THE FUGITIVE UNIT DOES NOT CONTAIN ANY EQUIPMENT IN ORGANIC HAZARDOUS AIR POLLUTANT (HAP) SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR</p> <p>ANY (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT PRESENT</p> <p>GAS VAPOR SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR VALVES</p> <p>AMEL = FUGITIVE UNIT SOURCE OWNER/OPERATOR IS NOT ELECTING TO COMPLY WITH AN ALTERNATIVE MEANS OF EMISSION LIMITATION (AMEL)</p> <p>FLARES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT</p> <p>LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (CONNECTORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT NOT PRESENT</p> <p>ANY (SAMPLING CONNECTION SYSTEMS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (SAMPLING CONNECTION SYSTEMS) = COMPONENT NOT PRESENT</p>	
VCM-9	40 CFR Part 63, Subpart H	63H-ALL-VCM-2	<p>ANY (CLOSED VENT SYSTEMS) = COMPONENT PRESENT</p> <p>ANY (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p> <p>BYPASS LINES = FUGITIVE UNIT WITH A CLOSED-VENT SYSTEM DOES NOT CONTAIN A BY-PASS LINE THAT COULD DIVERT A VENT STREAM AWAY FROM THE CONTROL DEVICE AND TO THE ATMOSPHERE</p> <p>EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (AGITATORS) = COMPONENT PRESENT</p> <p>LIGHT LIQUID SERVICE (PUMPS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (OPEN-ENDED VALVES OR LINES) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT</p> <p>NON RESEARCH AND DEVELOPMENT/BATCH PROCESSES = FUGITIVE UNIT</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>CONTAINS PROCESSES OTHER THAN RESEARCH AND DEVELOPMENT FACILITIES AND BENCH-SCALE BATCH PROCESSES</p> <p>RECOVERY OR RECAPTURE DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>UNSAFE TO INSPECT = FOR A FUGITIVE UNIT THAT CONTAINS ANY CLOSED-VENT SYSTEM, THERE ARE NO PARTS DESIGNATED AS UNSAFE TO INSPECT</p> <p>ANY (INSTRUMENTATION SYSTEMS) = COMPONENT PRESENT</p> <p>DIFFICULT TO INSPECT = FUGITIVE UNIT CONTAINS ANY CLOSED-VENT SYSTEM WITH PARTS DESIGNATED AS DIFFICULT TO INSPECT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (VALVES) = COMPONENT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR PUMPS</p> <p>VACUUM SERVICE = NOT ALL OF THE EQUIPMENT IN THE FUGITIVE UNIT IS IN VACUUM SERVICE</p> <p>ANY (COMPRESSORS) = COMPONENT PRESENT</p> <p>ENCLOSED COMBUSTION DEVICES (CLOSED VENT SYSTEMS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (VALVES) = COMPONENT NOT PRESENT</p> <p>LESS THAN 300 OPERATING HOURS = THE FUGITIVE UNIT DOES NOT CONTAIN ANY EQUIPMENT IN ORGANIC HAZARDOUS AIR POLLUTANT (HAP) SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR</p> <p>ANY (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT PRESENT</p> <p>GAS VAPOR SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR VALVES</p> <p>AMEL = FUGITIVE UNIT SOURCE OWNER/OPERATOR IS NOT ELECTING TO COMPLY WITH AN ALTERNATIVE MEANS OF EMISSION LIMITATION (AMEL)</p> <p>FLARES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT</p> <p>LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (CONNECTORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT NOT PRESENT</p> <p>ANY (SAMPLING CONNECTION SYSTEMS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (SAMPLING CONNECTION SYSTEMS) = COMPONENT NOT PRESENT</p>	
VCM-9	40 CFR Part 63, Subpart H	63H-ALL-VCM-23	<p>ANY (CLOSED VENT SYSTEMS) = COMPONENT PRESENT</p> <p>ANY (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>BYPASS LINES = FUGITIVE UNIT WITH A CLOSED-VENT SYSTEM DOES NOT CONTAIN A BY-PASS LINE THAT COULD DIVERT A VENT STREAM AWAY FROM THE CONTROL DEVICE AND TO THE ATMOSPHERE</p> <p>EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (AGITATORS) = COMPONENT PRESENT</p> <p>LIGHT LIQUID SERVICE (PUMPS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (OPEN-ENDED VALVES OR LINES) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT</p> <p>NON RESEARCH AND DEVELOPMENT/BATCH PROCESSES = FUGITIVE UNIT CONTAINS PROCESSES OTHER THAN RESEARCH AND DEVELOPMENT FACILITIES AND BENCH-SCALE BATCH PROCESSES</p> <p>RECOVERY OR RECAPTURE DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>UNSAFE TO INSPECT = FOR A FUGITIVE UNIT THAT CONTAINS ANY CLOSED-VENT SYSTEM, THERE ARE NO PARTS DESIGNATED AS UNSAFE TO INSPECT</p> <p>ANY (INSTRUMENTATION SYSTEMS) = COMPONENT PRESENT</p> <p>DIFFICULT TO INSPECT = FUGITIVE UNIT CONTAINS ANY CLOSED-VENT SYSTEM WITH PARTS DESIGNATED AS DIFFICULT TO INSPECT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (VALVES) = COMPONENT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR PUMPS</p> <p>VACUUM SERVICE = NOT ALL OF THE EQUIPMENT IN THE FUGITIVE UNIT IS IN VACUUM SERVICE</p> <p>ANY (COMPRESSORS) = COMPONENT PRESENT</p> <p>ENCLOSED COMBUSTION DEVICES (CLOSED VENT SYSTEMS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (VALVES) = COMPONENT NOT PRESENT</p> <p>LESS THAN 300 OPERATING HOURS = THE FUGITIVE UNIT DOES NOT CONTAIN ANY EQUIPMENT IN ORGANIC HAZARDOUS AIR POLLUTANT (HAP) SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR</p> <p>ANY (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT PRESENT</p> <p>GAS VAPOR SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR VALVES</p> <p>AMEL = FUGITIVE UNIT SOURCE OWNER/OPERATOR IS NOT ELECTING TO COMPLY WITH AN ALTERNATIVE MEANS OF EMISSION LIMITATION (AMEL)</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>FLARES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT</p> <p>LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (CONNECTORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT NOT PRESENT</p> <p>ANY (SAMPLING CONNECTION SYSTEMS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (SAMPLING CONNECTION SYSTEMS) = COMPONENT NOT PRESENT</p>	
D-104	30 TAC Chapter 115, Vent Gas Controls	R5121-6	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
GRPLUBVENT	30 TAC Chapter 115, Vent Gas Controls	R5121-LV	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
PRE-VCM-1	30 TAC Chapter 115, Vent Gas Controls	R5121-VCM-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
PRE-VCM-1	40 CFR Part 63, Subpart G	63G-3	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Halogenated = Vent stream is halogenated.</p> <p>Regulation = Owners or operator is required to comply only with the requirements of 40 CFR Part 63, Subpart G.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>TRE for Halogenated Vent Stream = The total resource effectiveness (TRE) index value is not being calculated for a halogenated vent stream.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>Halogen Reduction Device = The vent stream exiting the combustion device is ducted to a scrubber before it is discharged to the atmosphere.</p> <p>Installation Date = Prior to 12/31/92</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>	
PRE-VCM-2	30 TAC Chapter 115, Vent Gas Controls	R5121-VCM-2	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p>	
PRE-VCM-2	40 CFR Part 63, Subpart G	63G4	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Halogenated = Vent stream is halogenated.</p> <p>Regulation = Owners or operator is required to comply only with the requirements of 40 CFR Part 63, Subpart G.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>TRE for Halogenated Vent Stream = The total resource effectiveness (TRE) index value is not being calculated for a halogenated vent stream.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>vent stream from the control device.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>Halogen Reduction Device = The vent stream exiting the combustion device is ducted to a scrubber before it is discharged to the atmosphere.</p> <p>Installation Date = Prior to 12/31/92</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>	
PRE-VCM-23	30 TAC Chapter 115, Vent Gas Controls	R5121-VCM-23	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is greater than 100 pounds (45.4 kg).</p>	
PRE-VCM-23	40 CFR Part 63, Subpart G	63G5	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Thermal incinerator.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Halogenated = Vent stream is halogenated.</p> <p>Regulation = Owners or operator is required to comply only with the requirements of 40 CFR Part 63, Subpart G.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>TRE for Halogenated Vent Stream = The total resource effectiveness (TRE) index value is not being calculated for a halogenated vent stream.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>Halogen Reduction Device = The vent stream exiting the combustion device is ducted to a scrubber before it is discharged to the atmosphere.</p> <p>Installation Date = Prior to 12/31/92</p> <p>Performance Test = A performance test was conducted for determining compliance with a regulation promulgated by the EPA using the same methods specified in Subpart G and either no process changes have been made, or the results reliably indicate compliance.</p>	
UNIT 1	30 TAC Chapter 111, Visible Emissions	R1111-GT	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	
UNIT 2	30 TAC Chapter 111, Visible Emissions	R1111-GT	<p>Alternate Opacity Limitation = Not complying with an alternate opacity limit under 30 TAC § 111.113.</p> <p>Vent Source = The source of the vent is not a steam generator fired by solid fossil fuel, oil or a mixture of oil and gas and is not a catalyst regenerator for a fluid bed catalytic cracking unit.</p> <p>Opacity Monitoring System = Optical instrument capable of measuring the opacity of emissions is not installed in the vent or optical instrumentation does not meet the requirements of § 111.111(a)(1)(D), or the vent stream does not qualify for the exemption in § 111.111(a)(3).</p> <p>Construction Date = After January 31, 1972</p> <p>Effluent Flow Rate = Effluent flow rate is at least 100,000 actual cubic feet per minute.</p>	
VCM-22	30 TAC Chapter 115, Vent Gas Controls	R5121-12	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
VCM-5	30 TAC Chapter 115, Vent Gas Controls	R5121-10	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
VCM-6	30 TAC Chapter 115, Vent Gas Controls	R5121-11	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Vent Type = Vent gas stream emissions of the specified classes of VOCs including aldehydes, alcohols, aromatics, ethers, olefins, peroxides, amines, acids, esters, ketones, sulfides, and branched chain hydrocarbons (C8 and above).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>	
C-210	40 CFR Part 60, Subpart NNN	60NNN-1	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-210	40 CFR Part 60, Subpart NNN	60NNN-26	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-210	40 CFR Part 60, Subpart NNN	60NNN-51	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-22	40 CFR Part 60, Subpart NNN	60NNN-23	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-22	40 CFR Part 60, Subpart NNN	60NNN-24	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p>	
C-22	40 CFR Part 60, Subpart NNN	60NNN-48	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Total Design Capacity = 1 gigagram per year or greater. Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.	
C-220	40 CFR Part 60, Subpart NNN	60NNN-2	Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate. Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream. Construction/Modification Date = After December 30, 1983. TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device. Subpart NNN Control Device = Thermal incinerator. Vent Type = Vent is not regulated by Subpart NNN. Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3). Total Design Capacity = 1 gigagram per year or greater. Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.	
C-220	40 CFR Part 60, Subpart NNN	60NNN-27	Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate. Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream. Construction/Modification Date = After December 30, 1983. TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device. Subpart NNN Control Device = Thermal incinerator. Vent Type = Vent is not regulated by Subpart NNN. Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3). Total Design Capacity = 1 gigagram per year or greater. Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.	
C-220	40 CFR Part 60, Subpart NNN	60NNN-52	Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate. Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream. Construction/Modification Date = After December 30, 1983. TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device. Subpart NNN Control Device = Thermal incinerator. Vent Type = Vent is not regulated by Subpart NNN.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2210	40 CFR Part 60, Subpart NNN	60NNN-15	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2210	40 CFR Part 60, Subpart NNN	60NNN-40	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2210	40 CFR Part 60, Subpart NNN	60NNN-65	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-23	40 CFR Part 60, Subpart NNN	60NNN-24	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-23	40 CFR Part 60, Subpart NNN	60NNN-49	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-230	40 CFR Part 60, Subpart NNN	60NNN-28	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-230	40 CFR Part 60, Subpart NNN	60NNN-3	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-230	40 CFR Part 60, Subpart NNN	60NNN-53	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2372	40 CFR Part 60, Subpart NNN	60NNN-16	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2372	40 CFR Part 60, Subpart NNN	60NNN-41	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2372	40 CFR Part 60, Subpart NNN	60NNN-66	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-24	40 CFR Part 60, Subpart NNN	60NNN-25	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-24	40 CFR Part 60, Subpart NNN	60NNN-50	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-240	40 CFR Part 60, Subpart NNN	60NNN-29	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-240	40 CFR Part 60, Subpart NNN	60NNN-4	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-240	40 CFR Part 60, Subpart NNN	60NNN-54	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2410	40 CFR Part 60, Subpart NNN	60NNN-17	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2410	40 CFR Part 60, Subpart NNN	60NNN-42	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2410	40 CFR Part 60, Subpart NNN	60NNN-67	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2420	40 CFR Part 60, Subpart NNN	60NNN-18	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
C-2420	40 CFR Part 60, Subpart NNN	60NNN-43	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2420	40 CFR Part 60, Subpart NNN	60NNN-68	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2450	40 CFR Part 60, Subpart NNN	60NNN-19	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.	
C-2450	40 CFR Part 60, Subpart NNN	60NNN-44	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2450	40 CFR Part 60, Subpart NNN	60NNN-69	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2460	40 CFR Part 60, Subpart NNN	60NNN-20	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Total Design Capacity = 1 gigagram per year or greater. Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.	
C-2460	40 CFR Part 60, Subpart NNN	60NNN-45	Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate. Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream. Construction/Modification Date = After December 30, 1983. TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device. Subpart NNN Control Device = Thermal incinerator. Vent Type = Vent is not regulated by Subpart NNN. Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3). Total Design Capacity = 1 gigagram per year or greater. Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.	
C-2460	40 CFR Part 60, Subpart NNN	60NNN-70	Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate. Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream. Construction/Modification Date = After December 30, 1983. TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device. Subpart NNN Control Device = Thermal incinerator. Vent Type = Vent is not regulated by Subpart NNN. Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3). Total Design Capacity = 1 gigagram per year or greater. Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.	
C-2470	40 CFR Part 60, Subpart NNN	60NNN-21	Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate. Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream. Construction/Modification Date = After December 30, 1983. TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device. Subpart NNN Control Device = Thermal incinerator. Vent Type = Vent is not regulated by Subpart NNN.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2470	40 CFR Part 60, Subpart NNN	60NNN-46	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2470	40 CFR Part 60, Subpart NNN	60NNN-71	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2480	40 CFR Part 60, Subpart NNN	60NNN-22	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2480	40 CFR Part 60, Subpart NNN	60NNN-47	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-2480	40 CFR Part 60, Subpart NNN	60NNN-72	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-410	40 CFR Part 60, Subpart NNN	60NNN-30	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-410	40 CFR Part 60, Subpart NNN	60NNN-5	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-410	40 CFR Part 60, Subpart NNN	60NNN-55	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-420	40 CFR Part 60, Subpart NNN	60NNN-31	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-420	40 CFR Part 60, Subpart NNN	60NNN-56	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-420	40 CFR Part 60, Subpart NNN	60NNN-6	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-430	40 CFR Part 60, Subpart NNN	60NNN-32	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-430	40 CFR Part 60, Subpart NNN	60NNN-57	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-430	40 CFR Part 60, Subpart NNN	60NNN-7	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-440	40 CFR Part 60, Subpart NNN	60NNN-33	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-440	40 CFR Part 60, Subpart NNN	60NNN-58	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-440	40 CFR Part 60, Subpart NNN	60NNN-8	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-450	40 CFR Part 60, Subpart NNN	60NNN-34	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-450	40 CFR Part 60, Subpart NNN	60NNN-59	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-450	40 CFR Part 60, Subpart NNN	60NNN-9	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
C-460	40 CFR Part 60, Subpart NNN	60NNN-10	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-460	40 CFR Part 60, Subpart NNN	60NNN-35	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-460	40 CFR Part 60, Subpart NNN	60NNN-60	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.	
C-470	40 CFR Part 60, Subpart NNN	60NNN-11	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-470	40 CFR Part 60, Subpart NNN	60NNN-36	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-470	40 CFR Part 60, Subpart NNN	60NNN-61	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			Total Design Capacity = 1 gigagram per year or greater. Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.	
C-480	40 CFR Part 60, Subpart NNN	60NNN-12	Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate. Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream. Construction/Modification Date = After December 30, 1983. TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device. Subpart NNN Control Device = Thermal incinerator. Vent Type = Vent is not regulated by Subpart NNN. Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3). Total Design Capacity = 1 gigagram per year or greater. Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.	
C-480	40 CFR Part 60, Subpart NNN	60NNN-37	Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate. Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream. Construction/Modification Date = After December 30, 1983. TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device. Subpart NNN Control Device = Thermal incinerator. Vent Type = Vent is not regulated by Subpart NNN. Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3). Total Design Capacity = 1 gigagram per year or greater. Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.	
C-480	40 CFR Part 60, Subpart NNN	60NNN-62	Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate. Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream. Construction/Modification Date = After December 30, 1983. TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device. Subpart NNN Control Device = Thermal incinerator. Vent Type = Vent is not regulated by Subpart NNN.	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-522	40 CFR Part 60, Subpart NNN	60NNN-13	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-522	40 CFR Part 60, Subpart NNN	60NNN-38	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-522	40 CFR Part 60, Subpart NNN	60NNN-63	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-740	40 CFR Part 60, Subpart NNN	60NNN-14	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-740	40 CFR Part 60, Subpart NNN	60NNN-39	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p> <p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
C-740	40 CFR Part 60, Subpart NNN	60NNN-64	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value less than 8.0 from a halogenated vent stream.</p> <p>Construction/Modification Date = After December 30, 1983.</p> <p>TOC Reduction = Compliance is achieved by reducing total organic compound emissions (less methane and ethane) by 98 weight-percent or to a concentration of 20 ppmv dry basis corrected to 3 percent oxygen using a VOC emissions non-flare combustion control device.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Subpart NNN Control Device = Thermal incinerator.</p> <p>Vent Type = Vent is not regulated by Subpart NNN.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p>	
VCM1	40 CFR Part 61, Subpart F	61F-1	<p>Bulk Resin Reactor = The process does not include a bulk resin reactor or a nonbulk resin reactor not used as a stripper.</p> <p>Existing Source = The source is a new source.</p> <p>Product Produced = Ethylene dichloride by reaction of oxygen and hydrogen chloride with ethylene.</p> <p>EEP = The EPA Administrator has not approved equivalent equipment or procedures.</p> <p>Initial Startup = The initial startup date of the new source was on or after the effective date.</p> <p>Nonbulk Resin Reactor = The process does not include a nonbulk resin reactor used as a stripper.</p> <p>Reactor = The process does not include a reactor.</p> <p>Oxychlorination Reactor = The process contains an oxychlorination reactor.</p> <p>Stripper = The process does not include a stripper.</p> <p>Ethylene Dichloride Purification = The process contains equipment used in ethylene dichloride purification.</p>	
VCM1	40 CFR Part 61, Subpart F	61F-2	<p>Bulk Resin Reactor = The process does not include a bulk resin reactor or a nonbulk resin reactor not used as a stripper.</p> <p>Existing Source = The source is a new source.</p> <p>Product Produced = Vinyl chloride by any process.</p> <p>EEP = The EPA Administrator has not approved equivalent equipment or procedures.</p> <p>Initial Startup = The initial startup date of the new source was on or after the effective date.</p> <p>Nonbulk Resin Reactor = The process does not include a nonbulk resin reactor used as a stripper.</p> <p>Reactor = The process includes a reactor.</p> <p>Stripper = The process does not include a stripper.</p>	
VCM2	40 CFR Part 61, Subpart F	61F-3	<p>Bulk Resin Reactor = The process does not include a bulk resin reactor or a nonbulk resin reactor not used as a stripper.</p> <p>Existing Source = The source is a new source.</p> <p>Product Produced = Ethylene dichloride by reaction of oxygen and hydrogen chloride with ethylene.</p> <p>EEP = The EPA Administrator has not approved equivalent equipment or procedures.</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>Initial Startup = The initial startup date of the new source was on or after the effective date.</p> <p>Nonbulk Resin Reactor = The process does not include a nonbulk resin reactor used as a stripper.</p> <p>Reactor = The process does not include a reactor.</p> <p>Oxychlorination Reactor = The process contains an oxychlorination reactor.</p> <p>Stripper = The process does not include a stripper.</p> <p>Ethylene Dichloride Purification = The process contains equipment used in ethylene dichloride purification.</p>	
VCM2	40 CFR Part 61, Subpart F	61F-4	<p>Bulk Resin Reactor = The process does not include a bulk resin reactor or a nonbulk resin reactor not used as a stripper.</p> <p>Existing Source = The source is a new source.</p> <p>Product Produced = Vinyl chloride by any process.</p> <p>EEP = The EPA Administrator has not approved equivalent equipment or procedures.</p> <p>Initial Startup = The initial startup date of the new source was on or after the effective date.</p> <p>Nonbulk Resin Reactor = The process does not include a nonbulk resin reactor used as a stripper.</p> <p>Reactor = The process includes a reactor.</p> <p>Stripper = The process does not include a stripper.</p>	
VCM1	40 CFR Part 63, Subpart F	63F-2	<p>Applicable Chemicals = The chemical manufacturing process unit manufactures, as a primary product, one or more of the chemicals listed in 40 CFR § 63.100(b)(1)(i) or 40 CFR § 63.100(b)(1)(ii).</p> <p>Intervening Cooling Fluid = There is no intervening cooling fluid containing less than 5 percent by weight of total HAPs listed in Table 4 of 40 CFR Part 63, Subpart F, between the process and cooling water.</p> <p>Table 2 HAP = The chemical manufacturing process unit uses as a reactant or manufactures, as a product or co-product, one or more of the organic hazardous air pollutants in Table 2.</p> <p>Table 4 HAP Content = The recirculating heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 4 of title 40 CFR Part 63, Subpart F.</p> <p>Alternate Means of Emission Limitation = No alternative means of emission limitation has been approved by the EPA Administrator to achieve a reduction in organic HAP emission or no alternate has been requested.</p> <p>NPDES Permit = The once-through heat exchange system is not subject to NPDES permit with an allowable discharge limit of 1 part per million or less above influent concentration or 10 percent or less above influent concentration.</p> <p>Meets 40 CFR 63.104(a)(4)(i)-(iv) = The once-through heat exchange system is not subject to an NPDES permit that meets 40 CFR § 63.104(a)(4)(i) - (iv).</p> <p>Heat Exchange System = A heat exchange system is utilized.</p> <p>Table 9 HAP Content = The once-through heat exchange system is not used</p>	

Unit ID	Regulation	Index Number	Basis of Determination*	Changes and Exceptions to DSS**
			<p>exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 9 of 40 CFR Part 63, Subpart G.</p> <p>Cooling Water Monitored = The cooling water is not being monitored for the presence of one or more HAPs or other representative substances whose presence in cooling water indicates a leak.</p> <p>Cooling Water Pressure = The heat exchange system is not operated with the minimum pressure on the cooling water side at least 35 kilopascals greater than the maximum pressure on the process side.</p>	
VCM2	40 CFR Part 63, Subpart F	63F-3	<p>Applicable Chemicals = The chemical manufacturing process unit manufactures, as a primary product, one or more of the chemicals listed in 40 CFR § 63.100(b)(1)(i) or 40 CFR § 63.100(b)(1)(ii).</p> <p>Intervening Cooling Fluid = There is no intervening cooling fluid containing less than 5 percent by weight of total HAPs listed in Table 4 of 40 CFR Part 63, Subpart F, between the process and cooling water.</p> <p>Table 2 HAP = The chemical manufacturing process unit uses as a reactant or manufactures, as a product or co-product, one or more of the organic hazardous air pollutants in Table 2.</p> <p>Table 4 HAP Content = The recirculating heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 4 of title 40 CFR Part 63, Subpart F.</p> <p>Alternate Means of Emission Limitation = No alternative means of emission limitation has been approved by the EPA Administrator to achieve a reduction in organic HAP emission or no alternate has been requested.</p> <p>NPDES Permit = The once-through heat exchange system is not subject to NPDES permit with an allowable discharge limit of 1 part per million or less above influent concentration or 10 percent or less above influent concentration.</p> <p>Meets 40 CFR 63.104(a)(4)(i)-(iv) = The once-through heat exchange system is not subject to an NPDES permit that meets 40 CFR § 63.104(a)(4)(i) - (iv).</p> <p>Heat Exchange System = A heat exchange system is utilized.</p> <p>Table 9 HAP Content = The once-through heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 9 of 40 CFR Part 63, Subpart G.</p> <p>Cooling Water Monitored = The cooling water is not being monitored for the presence of one or more HAPs or other representative substances whose presence in cooling water indicates a leak.</p> <p>Cooling Water Pressure = The heat exchange system is not operated with the minimum pressure on the cooling water side at least 35 kilopascals greater than the maximum pressure on the process side.</p>	

* - The "unit attributes" or operating conditions that determine what requirements apply

** - Notes changes made to the automated results from the DSS, and a brief explanation why

NSR Versus Title V FOP

The state of Texas has two Air permitting programs, New Source Review (NSR) and Title V Federal Operating Permits. The two programs are substantially different both in intent and permit content.

NSR is a preconstruction permitting program authorized by the Texas Clean Air Act and Title I of the Federal Clean Air Act (FCAA). The processing of these permits is governed by 30 Texas Administrative Code (TAC) Chapter 116.111. The Title V Federal Operating Program is a federal program authorized under Title V of the FCAA that has been delegated to the state of Texas to administer and is governed by 30 TAC Chapter 122. The major differences between the two permitting programs are listed in the table below:

NSR Permit	Federal Operating Permit(FOP)
Issued Prior to new Construction or modification of an existing facility	For initial permit with application shield, can be issued after operation commences; significant revisions require approval prior to operation.
Authorizes air emissions	Codifies existing applicable requirements, does not authorize new emissions
Ensures issued permits are protective of the environment and human health by conducting a health effects review and that requirement for best available control technology (BACT) is implemented.	Applicable requirements listed in permit are used by the inspectors to ensure proper operation of the site as authorized. Ensures that adequate monitoring is in place to allow compliance determination with the FOP.
Up to two Public notices may be required. Opportunity for public comment and contested case hearings for some authorizations.	One public notice required. Opportunity for public comments. No contested case hearings.
Applies to all point source emissions in the state.	Applies to all major sources and some non-major sources identified by the EPA.
Applies to facilities: a portion of site or individual emission sources	One or multiple FOPs cover the entire site (consists of multiple facilities)
Permits include terms and conditions under which the applicant must construct and operate its various equipment and processes on a facility basis.	Permits include terms and conditions that specify the general operational requirements of the site; and also include codification of all applicable requirements for emission units at the site.
Opportunity for EPA review for Federal Prevention of Significant Deterioration (PSD) and Nonattainment (NA) permits for major sources.	Opportunity for EPA review, Affected states review, and a Public petition period for every FOP.
Permits have a table listing maximum emission limits for pollutants	Permit has an applicable requirements table and Periodic Monitoring (PM) / Compliance Assurance Monitoring (CAM) tables which document applicable monitoring requirements.
Permits can be altered or amended upon application by company. Permits must be issued before construction or modification of facilities can begin.	Permits can be revised through several revision processes, which provide for different levels of public notice and opportunity to comment. Changes that would be significant revisions require that a revised permit be issued before those changes can be operated.
NSR permits are issued independent of FOP requirements.	FOP are independent of NSR permits, but contain a list of all NSR permits incorporated by reference

New Source Review Requirements

Below is a list of the New Source Review (NSR) permits for the permitted area. These NSR permits are incorporated by reference into the operating permit and are enforceable under it. These permits can be found in the main TCEQ file room, located on the first floor of Building E, 12100 Park 35 Circle, Austin, Texas. The Public Education Program may be contacted at 1-800-687-4040 or the Air Permits Division (APD) may be contacted at 1-512-239-1250 for help with any question.

Additionally, the site contains emission units that are permitted by rule under the requirements of 30 TAC Chapter 106, Permits by Rule. The following table specifies the permits by rule that apply to the site. All current permits by rule are contained in Chapter 106. Outdated 30 TAC Chapter 106 permits by rule may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/old106list/index106.html

Outdated Standard Exemption lists may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/oldselist/se_index.html

The status of air permits and applications and a link to the Air Permits Remote Document Server is located at the following Web site:

www.tceq.texas.gov/permitting/air/nav/air_status_permits.html

Prevention of Significant Deterioration (PSD) Permits	
PSD Permit No.: PSDTX880	Issuance Date: 03/02/2012
Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 136971	Issuance Date: 11/23/2015
Authorization No.: 18432	Issuance Date: 08/18/2006
Authorization No.: 19169	Issuance Date: 05/05/2011
Authorization No.: 2339A	Issuance Date: 01/09/2017
Authorization No.: 35335	Issuance Date: 03/02/2012
Authorization No.: 47668	Issuance Date: 11/30/2006
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.227	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 03/14/1997
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.265	Version No./Date: 09/04/2000
Number: 106.355	Version No./Date: 11/01/2001
Number: 106.371	Version No./Date: 03/14/1997
Number: 106.373	Version No./Date: 09/04/2000
Number: 106.412	Version No./Date: 09/04/2000
Number: 106.433	Version No./Date: 09/04/2000
Number: 106.452	Version No./Date: 09/04/2000
Number: 106.454	Version No./Date: 09/04/2000
Number: 106.472	Version No./Date: 09/04/2000

Number: 106.511	Version No./Date: 09/04/2000
Number: 106.512	Version No./Date: 06/13/2001
Number: 61	Version No./Date: 09/12/1989
Number: 118	Version No./Date: 06/07/1996

Emission Units and Emission Points

In air permitting terminology, any source capable of generating emissions (for example, an engine or a sandblasting area) is called an Emission Unit. For purposes of Title V, emission units are specifically listed in the operating permit when they have applicable requirements other than New Source Review (NSR), or when they are listed in the permit shield table.

The actual physical location where the emissions enter the atmosphere (for example, an engine stack or a sand-blasting yard) is called an emission point. For New Source Review preconstruction permitting purposes, every emission unit has an associated emission point. Emission limits are listed in an NSR permit, associated with an emission point. This list of emission points and emission limits per pollutant is commonly referred to as the "Maximum Allowable Emission Rate Table", or "MAERT" for short. Specifically, the MAERT lists the Emission Point Number (EPN) that identifies the emission point, followed immediately by the Source Name, identifying the emission unit that is the source of those emissions on this table.

Thus, by reference, an emission unit in a Title V operating permit is linked by reference number to an NSR authorization, and its related emission point.

Monitoring Sufficiency

Federal and state rules, 40 CFR § 70.6(a)(3)(i)(B) and 30 TAC § 122.142(c) respectively, require that each federal operating permit include additional monitoring for applicable requirements that lack periodic or instrumental monitoring (which may include recordkeeping that serves as monitoring) that yields reliable data from a relevant time period that are representative of the emission unit's compliance with the applicable emission limitation or standard. Furthermore, the federal operating permit must include compliance assurance monitoring (CAM) requirements for emission sources that meet the applicability criteria of 40 CFR Part 64 in accordance with 40 CFR § 70.6(a)(3)(i)(A) and 30 TAC § 122.604(b).

With the exception of any emission units listed in the Periodic Monitoring or CAM Summaries in the FOP, the TCEQ Executive Director has determined that the permit contains sufficient monitoring, testing, recordkeeping, and reporting requirements that assure compliance with the applicable requirements. If applicable, each emission unit that requires additional monitoring in the form of periodic monitoring or CAM is described in further detail under the Rationale for CAM/PM Methods Selected section following this paragraph.

Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected

Compliance Assurance Monitoring (CAM):

Compliance Assurance Monitoring (CAM) is a federal monitoring program established under Title 40 Code of Federal Regulations Part 64 (40 CFR Part 64).

Emission units are subject to CAM requirements if they meet the following criteria:

1. the emission unit is subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement;
2. the emission unit uses a control device to achieve compliance with the emission limitation or standard specified in the applicable requirement; and

3. the emission unit has the pre-control device potential to emit greater than or equal to the amount in tons per year for a site to be classified as a major source.

The following table(s) identify the emission unit(s) that are subject to CAM:

Unit/Group/Process Information	
ID No.: PRE-VCM-1	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-VCM-1
Pollutant: VOC	Main Standard: § 115.121(c)(1)
Monitoring Information	
Indicator: Firebox temperature	
Minimum Frequency: Four times per hour	
Averaging Period: n/a	
Deviation Limit: Incinerator firebox temperature must be maintained at not less than 1,300 degrees F.	
Basis of CAM: It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.	

Unit/Group/Process Information	
ID No.: PRE-VCM-2	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-VCM-2
Pollutant: VOC	Main Standard: § 115.121(c)(1)
Monitoring Information	
Indicator: Firebox temperature	
Minimum Frequency: Four times per hour	
Averaging Period: n/a	
Deviation Limit: Incinerator firebox temperature must be maintained at not less than 1,300 degrees F.	
<p>Basis of CAM: It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: PRE-VCM-23	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-VCM-23
Pollutant: VOC	Main Standard: § 115.121(c)(1)
Monitoring Information	
Indicator: Firebox temperature	
Minimum Frequency: Four times per hour	
Averaging Period: n/a	
Deviation Limit: Incinerator firebox temperature must be maintained at not less than 1,300 degrees F.	
<p>Basis of CAM: It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

Periodic Monitoring:

The Federal Clean Air Act requires that each federal operating permit include monitoring sufficient to assure compliance with the terms and conditions of the permit. Most of the emission limits and standards applicable to emission units at Title V sources include adequate monitoring to show that the units meet the limits and standards. For those requirements that do not include monitoring, or where the monitoring is not sufficient to assure compliance, the federal operating permit must include such monitoring for the emission units affected. The following emission units are subject to periodic monitoring requirements because the emission units are subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement that does not already require monitoring, or the monitoring for the applicable requirement is not sufficient to assure compliance:

Unit/Group/Process Information	
ID No.: C-253	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-13
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
Basis of monitoring: It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-253	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-13
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Failure to repair the fill pipe prior to refilling the storage tank.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-253	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-13
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Failure to keep a record of tank construction specifications.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-253	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-7
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-253	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-7
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Failure to repair the fill pipe prior to refilling the storage tank.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-253	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-7
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Failure to keep a record of tank construction specifications.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-253	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-5
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-253	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-5
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Failure to repair the fill pipe prior to refilling the storage tank.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-253	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-5
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Failure to keep a record of tank construction specifications.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-710	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-23
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-710	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-16
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-710	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-11
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-711	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-24
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-711	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-17
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-711	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-12
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-712A	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-19
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-712A	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-12
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-712A	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-8
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-712B	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-20
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-712B	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-13
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-712B	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-9
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-714	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-25
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-714	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-18
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-714	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-13
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-720A	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-15
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-720A	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-40
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-720A	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-40
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Failure to repair the fill pipe prior to refilling the storage tank.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-720A	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-40
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Record of Tank Construction Specifications	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-720A	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-29
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-720A	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-29
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Failure to repair the fill pipe prior to refilling the storage tank.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-720A	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-29
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Record of Tank Construction Specifications	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-720A	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-8
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-720A	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-19
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-720A	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-19
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Failure to repair the fill pipe prior to refilling the storage tank.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-720A	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-19
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Record of Tank Construction Specifications	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-720A	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-6
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-720B	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-16
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-720B	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-16
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Failure to repair the fill pipe prior to refilling the storage tank.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-720B	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-16
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Failure to keep a record of tank construction specifications.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-720B	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-41
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-720B	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-41
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Failure to repair the fill pipe prior to refilling the storage tank.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-720B	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-41
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Failure to keep a record of tank construction specifications.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-720B	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-30
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-720B	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-9
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-720B	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-9
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Failure to repair the fill pipe prior to refilling the storage tank.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-720B	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-9
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Failure to keep a record of tank construction specifications.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-720B	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-20
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-720B	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-7
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: C-720B	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-7
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Structural Integrity of the Pipe	
Minimum Frequency: Emptied and degassed	
Averaging Period: n/a	
Deviation Limit: Failure to repair the fill pipe prior to refilling the storage tank.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: C-720B	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-7
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Record of Tank Construction Specifications	
Minimum Frequency: n/a	
Averaging Period: n/a	
Deviation Limit: Failure to keep a record of tank construction specifications.	
<p>Basis of monitoring:</p> <p>The periodic monitoring option provided for emission units using a submerged fill pipe is location of the submerged fill pipe and structural integrity of the pipe. The location and the integrity of the pipe ensure that loading operations are controlled to prevent splash fill and reduce generated vapors; therefore, less emissions are released to the atmosphere. This approach was included as an option by the EPA in the "Periodic Monitoring Technical Reference Document" (April 1999) to monitor VOC sources.</p>	

Unit/Group/Process Information	
ID No.: D-104A	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-33
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: It is a deviation if the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, if the seals are detached, or if there are holes or tears in the seal fabric.	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the “Periodic Monitoring Technical Reference Document” (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: D-104B	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-34
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: It is a deviation if the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, if the seals are detached, or if there are holes or tears in the seal fabric	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the “Periodic Monitoring Technical Reference Document” (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: D-104C	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-35
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Internal Floating Roof	
Minimum Frequency: annually	
Averaging Period: n/a	
Deviation Limit: It is a deviation if the roof is not floating on the surface of the VOC, if liquid has accumulated on the internal floating roof, if the seals are detached, or if there are holes or tears in the seal fabric	
<p>Basis of monitoring:</p> <p>The option to monitor VOC emissions by visually inspecting the external floating roof or the internal floating roof was included as an option by the EPA in the “Periodic Monitoring Technical Reference Document” (April 1999) to monitor VOC sources. If the external or internal floating roof is operating in accordance with its design it will meet its control efficiency. Visually inspecting the external floating roof or the internal floating roof is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; and 30 TAC Chapter 115. Measuring and recording the accumulated area of gaps if the tank is equipped with primary seals is commonly required in federal and state rules, including: 40 CFR Part 60, Subpart Kb; 40 CFR Part 61, Subpart Y; 40 CFR 63 Subparts VV, DD, and MMM; and 30 TAC Chapter 115.</p>	

Unit/Group/Process Information	
ID No.: D-2525A	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-29
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: D-2525A	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-21
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: D-2525A	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-14
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: D-2525B	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-30
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: D-2525B	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-22
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: D-2525B	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-15
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: D-525A	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-31
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: D-525A	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-23
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: D-525A	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-16
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: D-525B	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-32
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: D-525B	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-24
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: D-525B	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-17
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: D-540	
Control Device ID No.: VCM-1	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-1-7
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: D-540	
Control Device ID No.: VCM-2	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-2-2
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: D-540	
Control Device ID No.: VCM-23	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Storage of VOCs	SOP Index No.: R5112-3-1
Pollutant: VOC	Main Standard: § 115.112(c)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: Once per week	
Averaging Period: n/a*	
Deviation Limit: It is a deviation if the combustion temperature < 1300 F.	
<p>Basis of monitoring:</p> <p>It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: PLTBlast	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-PLTBlast
Pollutant: OPACITY	Main Standard: § 111.111(a)(8)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: quarterly	
Averaging Period: n/a	
Deviation Limit: Opacity limit of 30% for abrasive blast operations.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: PLTPAINT	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-PLTPAINT
Pollutant: OPACITY	Main Standard: § 111.111(a)(8)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: quarterly	
Averaging Period: n/a	
Deviation Limit: Opacity limit of 30% for paint operations.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: UNIT 1	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-GT
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Fuel type	
Minimum Frequency: Annually	
Averaging Period: N/A	
Deviation Limit: It is a deviation if a fuel other than natural gas or hydrogen is fired, either alone or in combination with these gases.	
Basis of monitoring: Industry has demonstrated through performance tests and historical data that opacity and particulate matter standards are consistently met when combustion units fire natural gas hydrogen only.	

Unit/Group/Process Information	
ID No.: UNIT 2	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-GT
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(C)
Monitoring Information	
Indicator: Fuel type	
Minimum Frequency: Annually	
Averaging Period: N/A	
Deviation Limit: It is a deviation if a fuel other than natural gas or hydrogen is fired, either alone or in combination with these gases.	
Basis of monitoring: Industry has demonstrated through performance tests and historical data that opacity and particulate matter standards are consistently met when combustion units fire natural gas or hydrogen only.	

Unit/Group/Process Information	
ID No.: VCM-20	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-VCM-20
Pollutant: OPACITY	Main Standard: § 111.111(a)(8)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: quarterly	
Averaging Period: n/a	
Deviation Limit: Opacity limit of 30% for limestone unloading operations.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: VCM-21	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-VCM-21
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Fuel type	
Minimum Frequency: quarterly	
Averaging Period: n/a	
Deviation Limit: It is a deviation if a fuel other than natural gas is fired.	
Basis of monitoring: Industry has demonstrated through performance tests and historical data that opacity and particulate matter standards are consistently met when combustion units fire natural gas only.	

Unit/Group/Process Information	
ID No.: VCM-4	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-VCM-4
Pollutant: OPACITY	Main Standard: § 111.111(a)(1)(B)
Monitoring Information	
Indicator: Fuel type	
Minimum Frequency: quarterly	
Averaging Period: n/a	
Deviation Limit: It is a deviation if a fuel other than natural gas is fired.	
Basis of monitoring: Industry has demonstrated through performance tests and historical data that opacity and particulate matter standards are consistently met when combustion units fire natural gas only.	

Unit/Group/Process Information	
ID No.: YARDBLAST	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-YARDBLAST
Pollutant: OPACITY	Main Standard: § 111.111(a)(8)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: quarterly	
Averaging Period: n/a	
Deviation Limit: Opacity limit of 30% for abrasive blast operations.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Unit/Group/Process Information	
ID No.: YARDPAIN	
Control Device ID No.: N/A	Control Device Type: N/A
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 111, Visible Emissions	SOP Index No.: R1111-YDPAIN
Pollutant: OPACITY	Main Standard: § 111.111(a)(8)(A)
Monitoring Information	
Indicator: Visible Emissions	
Minimum Frequency: n/a	
Averaging Period: quarterly	
Deviation Limit: Opacity limit of 30% for abrasive blast operations.	
<p>Basis of monitoring:</p> <p>The option to perform opacity readings or visible emissions to demonstrate compliance is consistent with EPA Reference Test Method 9 and 22. Opacity and visible emissions have been used as an indicator of particulate emissions in many federal rules including 40 CFR Part 60, Subpart F and Subpart HH. In addition, use of these indicators is consistent with the EPA's "Compliance Assurance Monitoring (CAM) Technical Guidance Document" (August 1998). Monitoring specifications and procedures for the opacity are consistent with federal requirements and include the EPA's Test Method 9 for determining opacity by visual observations and the requirements of 40 CFR § 60.13 for a continuous opacity monitoring system (COMS). The monitoring specifications and procedures for the visible emissions monitoring are similar to "EPA Reference Method 22" procedures.</p>	

Available Unit Attribute Forms

OP-UA1 - Miscellaneous and Generic Unit Attributes
OP-UA2 - Stationary Reciprocating Internal Combustion Engine Attributes
OP-UA3 - Storage Tank/Vessel Attributes
OP-UA4 - Loading/Unloading Operations Attributes
OP-UA5 - Process Heater/Furnace Attributes
OP-UA6 - Boiler/Steam Generator/Steam Generating Unit Attributes
OP-UA7 - Flare Attributes
OP-UA8 - Coal Preparation Plant Attributes
OP-UA9 - Nonmetallic Mineral Process Plant Attributes
OP-UA10 - Gas Sweetening/Sulfur Recovery Unit Attributes
OP-UA11 - Stationary Turbine Attributes
OP-UA12 - Fugitive Emission Unit Attributes
OP-UA13 - Industrial Process Cooling Tower Attributes
OP-UA14 - Water Separator Attributes
OP-UA15 - Emission Point/Stationary Vent/Distillation Operation/Process Vent Attributes
OP-UA16 - Solvent Degreasing Machine Attributes
OP-UA17 - Distillation Unit Attributes
OP-UA18 - Surface Coating Operations Attributes
OP-UA19 - Wastewater Unit Attributes
OP-UA20 - Asphalt Operations Attributes
OP-UA21 - Grain Elevator Attributes
OP-UA22 - Printing Attributes
OP-UA24 - Wool Fiberglass Insulation Manufacturing Plant Attributes
OP-UA25 - Synthetic Fiber Production Attributes
OP-UA26 - Electroplating and Anodizing Unit Attributes
OP-UA27 - Nitric Acid Manufacturing Attributes
OP-UA28 - Polymer Manufacturing Attributes
OP-UA29 - Glass Manufacturing Unit Attributes
OP-UA30 - Kraft, Soda, Sulfite, and Stand-Alone Semichemical Pulp Mill Attributes
OP-UA31 - Lead Smelting Attributes
OP-UA32 - Copper and Zinc Smelting/Brass and Bronze Production Attributes
OP-UA33 - Metallic Mineral Processing Plant Attributes
OP-UA34 - Pharmaceutical Manufacturing
OP-UA35 - Incinerator Attributes
OP-UA36 - Steel Plant Unit Attributes
OP-UA37 - Basic Oxygen Process Furnace Unit Attributes
OP-UA38 - Lead-Acid Battery Manufacturing Plant Attributes
OP-UA39 - Sterilization Source Attributes
OP-UA40 - Ferroalloy Production Facility Attributes
OP-UA41 - Dry Cleaning Facility Attributes
OP-UA42 - Phosphate Fertilizer Manufacturing Attributes
OP-UA43 - Sulfuric Acid Production Attributes
OP-UA44 - Municipal Solid Waste Landfill/Waste Disposal Site Attributes
OP-UA45 - Surface Impoundment Attributes
OP-UA46 - Epoxy Resins and Non-Nylon Polyamides Production Attributes
OP-UA47 - Ship Building and Ship Repair Unit Attributes
OP-UA48 - Air Oxidation Unit Process Attributes
OP-UA49 - Vacuum-Producing System Attributes
OP-UA50 - Fluid Catalytic Cracking Unit Catalyst Regenerator/Fuel Gas Combustion Device/Claus Sulfur Recovery Plant Attributes
OP-UA51 - Dryer/Kiln/Oven Attributes
OP-UA52 - Closed Vent Systems and Control Devices
OP-UA53 - Beryllium Processing Attributes

OP-UA54 - Mercury Chlor-Alkali Cell Attributes
OP-UA55 - Transfer System Attributes
OP-UA56 - Vinyl Chloride Process Attributes
OP-UA57 - Cleaning/Depainting Operation Attributes
OP-UA58 - Treatment Process Attributes
OP-UA59 - Coke By-Product Recovery Plant Attributes
OP-UA60 - Chemical Manufacturing Process Unit Attributes
OP-UA61 - Pulp, Paper, or Paperboard Producing Process Attributes
OP-UA62 - Glycol Dehydration Unit Attributes
OP-UA63 - Vegetable Oil Production Attributes